

County Surveyor's Record, Douglas County, Oregon

4

Dependent Resurvey of a Portion of the 6th Stan. Par. S., S. Bdy.
T. 27 S., R. 4 W.

CHAINS

A black oak, 22 ins. diam., bears N. 42° W., 108 lks. dist.,
marked with scribe marks R4W visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the
ground, with brass cap marked

| | |
|------|------|
| S | C |
| T27S | R4W |
| S 33 | S 34 |
| S 4 | S 3 |
| T28S | |
| 1958 | |

from which

A cedar, 15 ins. diam., bears N. 48° E., 119 lks. dist.,
marked T27S R4W S34 SC BT.

A cedar, 15 ins. diam., bears S. 23° E., 110 lks., dist.,
marked T28S R4W S3 SC BT.

A fir, 5 ins. diam., bears S. 69½° W., 137 lks. dist.,
marked T28S R4W S4 SC BT.

A fir, 13 ins. diam., bears N. 12° 45' W., 110 lks. dist.,
marked T27S R4W S33 SC BT.

The cor. falls at a fence corner with fences extending N., S., and W.

Land, mountainous. Soil, clay with outcropping of granite and quartz
Timber, scattering fir, cedar, maple, madrone and oak; undergrowth,
vinemaple, wildrose, salal, fern, poison oak, and chinquapin.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 4 W.
(Restoring the 1881 survey by William H. Byars)
(Same Cadastral Surveyors and Special Instructions)

From the ¼ sec. cor. of secs. 25 and 26, perpetuated and recorded
by J. H. Markham in 1958, at record bearing and distance from the
original SE. bearing tree, monumented with an iron pipe, 1 in.
diam., firmly set, 6 ins. above ground.

from which the original bearing tree:

A fir, 42 ins. diam., bears S. 60° E., 35 lks. dist., with
scribe marks ¼ S BT. visible on a bark blaze. Rescribed ¼ S
BT on a bark blaze by Markham in 1958.

and substantiated by:

A turnout hole, bears S. 35° W., 33 lks. dist.

bearing trees added by J. H. Markham, in 1958:

A white fir, 11 ins. diam., bears N. 9° E., 27½ lks. dist.,
marked ¼ S25 BT.

A white fir, 8 ins. diam., bears S. 60° W., 21 lks. dist.,
marked ¼ S26 BT.