


Dependnet Resurvey of a Portion of the Subdivisional Lines,  
T. 28 S., R. 4 W.

CHAINS

A white fir, 7 ins. diam., bears N. 29° W., 25 lks. dist., marked  $\frac{1}{4}$  S26 BT.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked



Reset iron pipe alongside iron post.

N. 1° 10' E., bet. secs. 25 and 26, marking and blazing true line.

Descend 71 ft. over NW. slope, through scattering timber and dense undergrowth, along E. edge of logged area.


13.37 Riser Creek, 10 lks. wide, course SW.; descend 12 ft. over SE. slope.

18.83 Top of ascent, slopes E.; descend 12 ft. over N. slope.

19.56 Creek, 3 lks. wide; course E.; ascend 359 ft. over SE. slope changing to E. slope.

38.80 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked



from which

A pine, 5 ins. diam., bears N.  $55\frac{1}{4}$ ° E., 27 lks. dist., marked T28S R4W S24 BT.

A madrone, 8 ins. diam., bears S.  $56\frac{1}{2}$ ° E., 63 lks. dist., marked T28S R4W S25 BT.

A pine, 6 ins. diam., bears S.  $50\frac{1}{4}$ ° W., 60 lks. dist., marked T28S R4W S26 BT.

A fir, 36 ins. diam., bears N. 45° W., 42 lks. dist., marked T28S R4W S23 BT.

Land, mountainous. Soil, clay and rocky clay. Timber, fir, cedar, hemlock, madrone and alder; undergrowth, fern, vinemaple, hazel, poison oak and conifer reproduction.

From the cor. of secs. 24 and 25 only, on E. bdy. of Tp., determined at record distance from the remaining original bearing trees and substantiated by the stump holes of the two bearing trees destroyed by Gibb, in 1908 retracement of the E. bdy. of the Tp., as follows:

A fir, 32 ins. diam., bears N, 84° W., 17 lks. dist., with healed blaze. (Record bearing N. 75° W.)