

County Surveyor's Record, Douglas County, Oregon  
6

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

A fir, 22 ins. diam., bears S. 71° W., 16 lks. dist., with healed blaze. (Record bearing S. 35° W.)

and substantiating evidences:

A stump hole, bears N. 5° E., 19 lks. dist.

A stump hole, bears S. 25° E., 22 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T28S		T28S
S 24		S 30
S 25		R4W R3W
		1958

S. 89° 42' W., bet. secs. 24 and 25.

Ascend 211 ft. over E. slope changing to SE. slope, through heavy timber and dense undergrowth.

- 11.70 Spur, slopes S.; descend 113 ft. over SW. slope.
- 16.06 Ravine, drains S.; ascend 88 ft. over SE. slope.
- 19.37 Spur, slopes S.; descend 81 ft. over SW. slope.
- 22.21 Ravine, drains S.; ascend 52 ft. over SE. slope.
- 24.05 Spur, slopes S.; descend 14 ft. over SW. slope.
- 25.53 Draw, course S.; ascend 214 ft. over E. slope.
- 32.30 Spur ridge, dividing Slide Creek drainage and Riser Creek drainage, bears NE. and SW.; descend 208 ft. over NW. slope.
- 39.215 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. the ground, with brass cap marked

T28S R4W

¼		S 24
		S 25

1958

from which

Af A fir, 19 ins. diam., bears N. 83¼° W., 93 lks. dist., marked ¼ S24 BT.

A fir, 8 ins. diam., bears S. 12 ¾° W., 32 lks. dist., marked ¼ S25 BT.

Descend 117 ft. over W. slope.

- 40.91 Ravine, drains NW.; descend 80 ft. over NW. slope.
- 44.83 Ravine, drains NW.; ascend 2 ft. over NE. slope.