

## County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

46.05 Top of ascent, slopes N.; descend 156 ft. along N. slope changing to NW. slope.

53.87 Ravine, drains NW.; descend 101 ft. over W. slope.

61.36 Riser Creek, 10 lks. wide, course S. curving to SW.; ascend 95 ft. over SE. slope.

65.69 Spring branch, 1 lk. wide, course S. 70° E.; ascend 227 ft. over SE. slope changing to S. slope.

78.43 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous. Clay and clay loam. Timber, fir, hemlock, cedar, madrone, maple and dogwood; undergrowth, vinamaple, fern, hazel, arrowwood, salal, poison oak, Oregon grape, blackberry, manzanita, and rhododendron.

N. 1° 12' E., bet. 23 and 24.

Ascend 89 ft. along E. slope changing to SE. slope, through heavy timber and dense undergrowth.

3.98 Spur, slopes SE.; descend 9 ft. along E. slope.

7.17 Ravine, drains SE.; ascend 224 ft. over SE. slope.

14.40 Ridge, dividing North Myrtle Creek drainage and Riser Creek drainage, bears NE. and SW.; descend 166 ft. over NW. slope.

19.40 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{S } 1/16 \\ | \\ \text{S } 23 \text{ | } \text{S } 24 \\ | \\ 1958 \end{array}$$

from which

A fir, 20 ins. diam., bears N. 26½° E., 24 lks. dist., marked S 1/16 S24 BT.

A fir, 15 ins. diam., bears N. 24½° W., 46 lks. dist., marked S 1/16 S23 BT.

Descend 491 ft. over N. slope changing to NE. slope.

31.44 Ravine, drains NW.; descend 59 ft. over NW. slope.

35.81 Leave timber, enter bottom land, edge bears NE. and SW.

38.80 The ¼ sec. cor. of secs. 23 and 24, perpetuated and recorded by J. H. Markham in 1953, at record bearing and distance from the original SE. bearing tree, monumented with an iron pipe 1 in. diam., firmly set, 8 ins. above ground.

from which the original bearing tree:

A fir, 33 ins. diam., bears S. 65° E., 22 lks. dist., with partially opened blaze, no scribe marks visible. Rescribed ¼ S24 BT on a bark blaze by Markham.

bearing tree by Markham:

A cedar, 11 ins. diam., bears S. 47° W., 77½ lks. dist., with scribe marks ¼ S23 BT visible on partially healed blaze.