


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

- CHAINS
- 15.29 Enter scattered timber, edge bears E. and W.
 - 22.83 Leave timber and undergrowth, enter open pasture land, edge bears NE. and SW.
 - 27.56 Dirt access road, 12 lks. wide, bears NE. and SW.
 - 28.76 Leave pasture land, enter undergrowth, edge bears E. and W.
 - 31.20 Slide Creek, 14 lks. wide, course SW.; Leave undergrowth, enter pasture land, edge bears NE. and SW.; ascend 13 ft. over S. slope.
 - 32.59 Irrigation ditch, 8 lks. wide, course NW.; ascend 27 ft. over SE. slope.
 - 34.68 The NW. cor. of a wood frame sheep feeding shed on line, dimensions 61 x 16 $\frac{1}{2}$ ft., long side bears NE.
 - 35.17 Wooden corral fence, bears NW. and SE.
 - 35.56 Wooden corral fence, bears NE. and SW.
 - 36.97 Maintained gravel access road, 15 lks. wide, bears NE. and SW.
 - 38.34 Spring branch, 1 lk. wide, course SE.; ascend 21 ft. over SE. slope.
 - 39.24 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, perpetuated and recorded by G. G. Stewart, C. S., in 1922 at record bearing and distance from the original bearing trees, of which the NE. tree is no longer in existence, monumented with an iron pipe $\frac{1}{2}$ in. diam., firmly set, 2 ins. above ground, and remonumented by J. W. Bryon, D.C.S., in 1958, with an iron post, 1 in. diam., firmly set 12 ins. above ground, with brass cap marked



from which the original bearing trees:

A rotted sawed fir stump, 24 ins. diam., bears S. 89° W., 19 lks. dist., no scribe marks visible.

bearing trees by Stewart in 1922:

A fir, 37 ins. diam., bears N. 26 $\frac{1}{2}$ ° E., 74 lks. dist., with scribe marks $\frac{1}{4}$ CS BT. visible on bark blaze.

A sawed fir stump, 25 ins. diam., bears S. 64° W., 51 $\frac{1}{2}$ lks. dist., no scribe marks visible.

bearing trees by Bryon in 1958:

A cedar, 13 ins. diam., bears N. 34° E., 74 lks. dist., marked $\frac{1}{4}$ S35 CS BT. on open blaze.

A fir, 22 ins. diam., bears S. 49° E., 69 lks. dist., marked $\frac{1}{4}$ S35 CS BT. on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked