

County Surveyor's Record, Douglas County, Oregon

11

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

Ascend 126 ft. over SE. slope, through scattered timber and undergrowth, along the N. edge of logged area.

2.88 Spur, slopes S.; descend 121 ft. over SW. slope.

9.00 Ravine, drains S.; ascend 42 ft. over SE. slope.

11.10 Spur, slopes S.; descend 28 ft. over SW. slope.

13.05 Ravine, drains S.; ascend 28 ft. over SE. slope.

14.70 Top of ascent, slopes S.; descend 12 ft. over SW. slope.

18.20 Foot of descent, slopes S.; ascend 9 ft. over SE. slope.

19.605 Point for the E. 1/16 sec. cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

E 1/16 $\frac{S\ 23}{S\ 26}$

1958

from which

A white fir, 8 ins. diam., bears N. 17½° E., 34 lks. dist., marked E 1/16 S23 BT.

A white fir, 6 ins. diam., bears S. 53° E., 27 lks. dist., marked E 1/16 S26 BT.

Ascend 144 ft. over SE. slope changing to E. slope.

28.96 Ridge, dividing Riser Creek drainage and North Myrtle Creek drainage, bears NE. and SW.; descend 406 ft. over W. slope.

37.85 Ravine, drains NW.; ascend 41 ft. over NE. slope.

39.21 The ¼ sec. cor. of secs. 23 and 26, recorded and perpetuated by H. L. Eppstein, C. S. in 1935, at record bearing and dist. from the original SE. bearing tree, and again recorded and remonumented by J. W. Bryon, D.C.S., in 1957, with an iron pipe, 1 in. diam., firmly set 8 ins. above ground, with brass cap marked

County Surveyors

T28S R4W

 $\frac{S\ 23}{S\ 26}$

Office 1957

from which the original bearing tree:

A turnout hole, bears S. 15° E., 33 lks. dist., the tree a fir 30 ins. diam., has slid 30 ft. down hill, with scribe marks ¼ S BT visible on bark blaze.

and substantiated by:

A burned fir snag, 30 ins. diam., bears N. 46° W., 56 lks. dist., no scribe marks visible. (Record N. 54° W.)

bearing trees by Eppstein, in 1935:

A fir, , 33 ins. diam., bears S. 3° E., 45 lks. dist., with scribe marks ¼ S CS BT visible on partially healed blaze.

bearing tree by Bryon, in 1957: A hemlock, 11 ins. diam., bears N. 58° E., 29 lks. dist., with scribe marks ¼ S23 CS BT visible on partially healed blaze.

At the corner point