

County Surveyor's Record, Douglas County, Oregon

Dependant Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.


CHAINS

A cedar, 7 ins. diam., bears S. 78° E., 62½ lks. dist., marked  
¼ S27 CS BT.

A fir, 16 ins. diam., bears S. 20½° W., 42 lks. dist., marked  
¼ S28 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground,  
with brass cap marked



Reset county surveyors post alongside iron post.

N. 0° 03' W., beginning new measurement.

Ascend 283 ft. over broken SW. slope, along E. edge of logged area,  
through scattering timber and dense undergrowth.

25.09 Spur, slopes SW.; descend 130 ft. over NW. slope.

27.32 Ravine, drains N. 20° W.; descend 183 ft. over broken NW. slope.

39.27 The cor. of secs. 21, 22, 27 and 28, perpetuated and recorded by J.  
H. Markham, in 1950, at record bearing and distance from the orig-  
inal SE. bearing tree, monumented with an iron pipe, 1½ ins. diam.,  
firmly set, 12 ins. above ground; from which the original bearing  
tree;

A turned out fir snag, 26 ins. diam., bears S. 80° E., 22 lks.  
dist., no scribe marks visible.

bearing trees by Markham, in 1950:

A fir, 31 ins. diam. bears S. 50° E., 100 lks. dist., with  
scribe marks S27 28 visible on bark blaze.


A fir, 42 ins. diam., bears S. 29½° E., 54 lks. dist., with  
scribe marks S 27 28S visible on bark blaze.

A sawed fir stump, 30 ins. diam., bears N. 35° W., 34 lks. dist.,  
with scribe marks BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins diam., 24 ins. in the  
ground, with brass cap marked

*FD OK 1-93  
R. Brown  
M 116-52*



from which bearing trees:

An alder, 7 ins. diam., bears N. 13½° E., 75 lks. dist.,  
marked T28S R4W S22 BT.

A fir, 7 ins. diam., bears S. 66° W., 138 lks. dist., marked  
T28S R4W S28 BT.

A fir, 35 ins. diam., bears N. 58 3/4° W., 122 lks. dist.,  
marked T28S R4W S21 BT.

Reset iron pipe alongside iron post.