


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

- 36.65 Spur, slopes SE.; descend 23 ft. Over NE. slope.
- 37.85 Skid road, 10 lks. wide, bears E. and W.
- 39.18 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

*PLUCK 8/92
BY BLUNTZ M115-5A*



*FD OK 3/86
M100-97
H. Johnson*

from which

A fir, 10 ins. diam., bears S. 87° E., 59 lks. dist., marked $\frac{1}{4}$ S22 BT.

A fir, 12 ins. diam., bears S. 66° W., 32 lks. dist., marked $\frac{1}{4}$ S21 BT.

From this point a locally established cor. bears N. $35^{\circ} 41'$ W., 88 lks. dist., monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, 12 ins. above ground, from which

A maple, 9 ins. diam., bears S. $88\frac{1}{2}^{\circ}$ E., 25 lks. dist., with scribe marks $\frac{1}{4}$ S 2880 visible on an unhealed blaze.

A madrone, 6 ins. diam., bears E., 9 lks. dist., bark scribed $\frac{1}{4}$ S.

A fir, 11 ins. diam., bears N. $41\frac{3}{4}^{\circ}$ W., 44 lks. dist., bark scribed $\frac{1}{4}$ S 2880.

Descend 56 ft. over NE. slope.

- 43.06 Ravine, drains E.; ascend 37 ft. over SE. slope.
- 43.80 Spur, slopes SE.; ascend 85 ft. over SE. slope.
- 49.00 Ravine, drains S. 30° E.; ascend 255 ft. over SW. slope.
- 56.55 Spur, slopes SE.; ascend 55 ft. over SE. slope.
- 61.30 Spur, slopes S. 60° E.; descend 219 ft. over NE. slope.
- 67.50 Ravine, drains E.; ascend 16 ft. along E. slope.
- 70.84 Spur, slopes E.; descend 88 ft. over NE. slope.
- 75.00 Ravine, drains E.; ascend 9 ft. over SE. slope.
- 76.70 Spur, slopes S. 50° E.; descend 42 ft. over NE. slope.
- 78.36 The cor. of secs. 15, 16, 21 and 22, perpetuated and recorded by J. H. Markham, in 1950, at record bearing and distance from the original SW. bearing tree and monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, 8 ins. above ground, from which the original bearing tree:
A cedar snag, dead and fallen, 18 ins. diam., bears S. 88° W., 40 lks. dist., with illegible scribe marks visible on an open face.

and locally established bearing trees: