

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

A cedar, 5 ins. diam., bears N. 74° E., 14 lks. dist., marked 2880 S22 on an unhealed blaze.

A sawed hemlock stump, 30 ins. diam., bears S. 38° E., 34 lks. dist., marked S21 on unhealed blaze.

A cedar, 15 ins. diam., bears N. 83° W., 60 lks. dist., marked S21 2880 BT. on unhealed blaze.

A fir snag, 16 ins. diam., bears N. 14° 45' W., 26 lks. dist., marked S16.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

FD OK PER BEUTZ
1-89 m107-48

T28S R4W
S 16 S 15
S 21 S 22
1958

from which

A fir, 8 ins. diam., bears N. 27° 45' E., 66 lks. dist., marked T28S R4W S15 BT.

A hemlock, 7 ins. diam., bears S. 29½° E., 44½ lks. dist., marked T28S R4W S22 BT.

A white fir, 21 ins. diam., bears S. 84½° W., 73 lks. dist., marked T28S R4W S21 BT.

A fir, 25 ins. diam., bears N. 50° 45' W., 73 lks. dist., marked T28S R4W S16 BT.

Deposit iron pipe alongside iron post.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, maple and madrone; undergrowth, hazel, salal, madrone and poison oak.

N. 0° 46' E., bet. secs. 15 and 16.

Ascend 1 ft. over SE. slope., through heavy timber and dense undergrowth.

- 1.40 Spur, slopes S. 50° E.; descend 19 ft. over NE. slope.
- 2.05 Spring branch, 2 lks. wide, course E.; ascend 9 ft. along E. slope.
- 12.30 Creek, 8 lks. wide, course SE.; ascend 250 ft. over SW. slope.
- 19.25 Spur, slopes S. 50° W.; ascend 145 ft. along W. slope, changing to SW. slope.
- 32.05 Top of ascent, slopes W.; descend 60 ft. over NW. slope.
- 39.28 The ¼ sec. cor. of secs. 15 and 16, determined at record distance from two original bearing trees, as follows:

A cedar, 40 ins. diam., bears N. 74° E., 48 lks. dist., bark scribed ¼ S BT, (Record bearing N. 50° E.)

A fir, 45 ins. diam., bears S. 52° W., 37 lks. dist., with old axe marks and a healed blaze, (Record bearing S. 45° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked