


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS



from which

A fir, 14 ins. diam., bears N. 66° W., 10 $\frac{1}{4}$  lks. dist., marked  $\frac{1}{4}$  S16 BT.

A fir, 16 ins. diam., bears S. 51 $\frac{1}{2}$ ° E., 29 $\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S15 BT.


-----

N. 0° 18' W., beginning new measurement.

Descend 2 ft. over NW. slope.

- 0.80 Spring branch, 1 lk. wide, course S. 60° W.; ascend 268 ft. over SW. slope changing to S. slope.
- 12.00 Head of ravine, drains SW.; ascend 72 ft. over SW. slope.
- 14.60 Spur, slopes S. 30° W.; ascend 3 ft. along W. slope.
- 18.20 Ravine, drains S. 70° W.; ascend 133 ft. over SW. slope.
- 23.50 Spur, slopes S. 70° W.; ascend 246 ft. along W. slope changing to SW. slope.
- 39.22 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked



from which

A fir, 9 ins. diam., bears N. 17° E., 94 $\frac{1}{2}$  lks. dist., marked T28S R4W S10 BT.

A fir, 13 ins. diam., bears S. 22° E., 80 lks. dist., marked T28S R4W S15 BT.

A cedar, 11 ins. diam., bears S. 39° W., 69 lks. dist., marked T28S R4W S16 BT.

A fir, 13 ins. diam., bears N. 36° W., 73 $\frac{1}{2}$  lks. dist., marked T28S R4W S 9 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, madrone; undergrowth, salal, poison oak, hazel and madrone.

From the cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by J. W. Byron, in 1957, at record bearing and distance from three original bearing trees, and at record bearing from the fourth original bearing tree, monumented with an iron post, 1 in. diam., firmly set, 8 ins. above ground, with brass cap marked

County Surveyors  
 T28S R4W  
 SEC 10 | 11  
 COR 15 | 14  
 1957  
 Office