

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS


- 26.20 Ravine, drains SE.; ascend 287 ft. over SE. slope.
- 33.80 Ridge, bears N. 55° E.; and S. 55° W.; descend 162 ft. over NW. slope.
- 39.22 The 1/4 sec. cor. of secs. 9 and 10, determined at record bearing and distance from the original bearing trees, as follows:

A fir, 63 ins. diam., bears N. 25° E., 78 lks. dist., with axe marks and illegible scribe marks on a double bark blaze.

A fir, 75 ins. diam., bears N. 40° W., 10 lks. dist., with axe marks and a double bark blaze, no scribe marks visible.

At corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked



*Fwd. OK by
BURT. HOLT
M 90-5
10/81*

from which

A fir, 27 ins. diam., bears S. 58° E., 34 lks. dist., marked 1/4 S10 BT.


A fir, 23 ins. diam., bears S. 24° 45' W., 44 1/2 lks. dist., marked 1/4 S9 BT.

N. 0° 12' E., beginning new measurement.

Descend 226 ft. over NW. slope, through heavy timber and dense undergrowth.

- 7.20 Spur, slopes N. 20° W.; descend 293 ft. over NE. slope.
- 16.45 Spring branch, 1 lk. wide, course NW.; ascend 4 ft. over SW. slope.
- 19.165 Point for the N 1/16 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked.



*See map of
...
...
...*

*COR RE
...
7/16/72
w/ W.C.
CO. REC. 113*

from which

A fir, 10 ins. diam., bears N. 26 1/2° E., 28 1/2 lks. dist., marked N 1/16 S10 BT.

A fir, 7 ins. diam., bears N. 81 1/2° W., 15 3/4 lks. dist., marked N1/16 S9 BT.

Ascend 9 ft. over SW. slope.

- 21.20 Spur, slopes NW.; descend 29 ft. over NE. slope.
- 22.20 Ravine, drains NW.; ascend 39 ft. over NW. slope.
- 28.50 Top of ascent, slopes N. 60° W.; descend 187 ft. over NW. slope.
- 36.05 Spur, slopes NW.; descend 88 ft. over NE. slope.