

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

38.33

The cor. of secs. 3, 4, 9 and 10, perpetuated with a granite boulder 18x12x10 ins., above ground, firmly set, from which four original bearing trees, as follows:

A fir snag, 35 ins. diam., bears N. 84° 45' E., 102 1/4 lks., dist., bark scribed S3 T28S R4W. (Record bearing and distance, N. 76° E., 100 lks.)

A fir, 47 ins. diam., bears S. 60° E., 56 lks. dist., bark scribed S10 T28S R4W BT.

A fir snag, 32 ins. diam., bears S. 11 1/2° W., 34 lks. dist., (38 lks. dist. to the face on the slope,) (Record bearing and distance S. 10° W., 38 lks.) bark scribed S T28S R4W.

A fir, 58 ins. diam., bears N. 12° W., 40 1/2 lks. dist., with a healed blaze. (Record distance 37 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked

*Fnd. OK. by 10/81
BURT. HOLT
90-5
M*

T28S R4W
S 4 | S 3
S 9 | S 10
1958

from which

A fir, 12 ins. diam., bears N. 60° E., 26 1/2 lks. dist., marked T28S R4W S3 BT.

A cedar, 10 ins. diam., bears S. 19° 45' W., 53 lks. dist., marked T28S R4W S9 BT.

Deposit the granite boulder alongside iron post.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, madrone and maple; undergrowth, salal, huckleberry, hazel, madrone and vinemaple.

From the cor. of secs. 2, 3, 10 and 11, determined at record distance from the faces of four original bearing trees, as follows:

A cedar snag, 9 ins. diam., bears N. 56 1/4° E., 31 lks. dist., scribed 28S R4W. (Record bearing and distance, N. 50° E., 30 lks.)

A fir, 22 ins. diam., bears S. 32° E., 37 1/2 lks. dist., bark scribed S11 T28S R4W BT. (Record bearing and distance, S. 42° E., 36 lks. dist.)

A fir, 32 ins. diam., bears S. 28 1/4° W., 47 1/2 lks. dist., bark scribed S10 T28S R4W BT. (Record bearing and distance, S. 20° W., 45 lks. dist.)

A fir, 24 ins. diam., bears N. 40° W., 8 1/2 lks. dist., bark scribed T28S R4W BT. (Record distance, 7 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked

*Fnd. OK. by 10/81
BURT. HOLT
90-5
M*

T28S R4W
S 3 | S 2
S 10 | S 11
1958

from which