

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS	<p>A cedar, 13 ins. diam., bears N. 20°45'E., 144½ lks. dist., marked T28S R4W S2 BT.</p> <p>A fir, 30 ins. diam., bears N. 51° 45' W., 43 lks. dist., marked T28S R4W S3 BT.</p> <p>N. 89° 20' W., bet. secs. 3 and 10</p> <p>Ascend 61 ft. over SE. slope, through heavy timber and scattering undergrowth.</p> <p>3.45 Ridge, bears N. 20° E. and S. 30° W.; descend 351 ft. over NW. slope.</p> <p>4.10 Dirt access road, 20 lks. wide, bears E. 30° E. and S. 30° W.</p> <p>14.45 Skid road, 15 lks. wide, bears NW. and S. 70° E.</p> <p>21.70 Spur, slopes NW.; descend 90 ft. over NW. slope.</p> <p>24.55 Spring branch, 1 lk. wide, course N. 30° W.; ascend 83 ft. over NE. slope.</p> <p>32.20 Spur, slopes N. 30° W.; descend 198 ft. over NW. slope.</p> <p>38.00 Ravine, drains N. 20° W.; Ascend 26 ft. along N. slope.</p> <p>38.91 The ¼ sec. cor. of secs. 3 and 10, determined at record distance from two original bearing trees, as follows:</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears N. 50° W., 20 lks. dist., with illegible scribe marks visible on opened blaze.</p> <p style="padding-left: 40px;">A burned and rotted cedar stump, 18 ins. diam., bears S. 89½° E., 28 lks. dist., no scribe marks visible. (Record bearing S.87°E.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <p>T28S R4W</p> <p>¼ $\frac{S\ 3}{S\ 10}$</p> <p>1958</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears N. 61° W., 27 lks. dist., marked ¼ S3 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 4° 45' E., 63 lks. dist., marked ¼ S10 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 47' W., beginning new measurement.</p> <p>Descend 57 ft. over NW. slope.</p> <p>1.35 Creek, 2 lks. wide, course N.; ascend 45 ft. over NE. slope.</p> <p>3.00 Spur, slopes N. 10° W.; descend 45 ft. over NW. slope.</p> <p>4.90 Ravine, drains N.; ascend 64 ft. over NE. slope.</p> <p>7.50 Spur, slopes N. 30° W.; descend 209 ft. over W. slope.</p> <p>13.85 Creek, 1 lk. wide, course S. 70° W.; descend 86 ft. over SW. slope.</p> <p>17.75 Creek, 2 lks. wide, course N. 50° W.; ascend 25 ft. along N. slope.</p> <p>19.115 Point for the W 1/16 sec. cor. of secs. 3 and 10.</p>
--------	--

*Fnd. OK by
Burt. Holt
M 90-5
10/61*