

## Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

## CHAINS.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground with brass cap marked

W 1/16  $\begin{matrix} S 3 \\ S 10 \end{matrix}$   
1958

from which

A cedar, 8 ins. diam., bears North, 17 lks. dist., marked W 1/16 S3 BT.

A hemlock, 18 ins. diam., bears S.  $14\frac{1}{2}^{\circ}$  E., 39 lks. dist., marked W 1/16 S10 BT.

Cor. falls on a spur, slopes N.  $30^{\circ}$  W.

Descend 78 ft. over NW. slope.

20.75 Creek, 3 lks. wide, course N.; ascend 82 ft. over NE. slope.

23.05 Spur, slopes N.; descend 30 ft. over NW. slope.

24.10 Ravine, drains N.  $20^{\circ}$  E.; ascend 191 ft. over NE. slope.

30.10 Spur, slopes N.; descend 219 ft. over NW. slope.

38.23 The cor. of secs. 3, 4, 9 and 10.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, madrone, and yew; undergrowth, fern, oceanspray, hazel, salal, chinquapin, alder and manzanita.

N.  $2^{\circ} 08'$  E., bet. secs. 3 and 4.

Descend 355 ft. over N. slope.

6.95 Creek, 5 lks. wide, course W.; ascend 442 ft. over S. slope changing to SE. slope.

22.15 Top of ascent, slopes E.; descend 57 ft. over NE. slope.

27.25 Ravine, course E.; ascend 125 ft. over SE. slope.

40.64 The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, monumented by the original cor. tree, a chopped fir stump, 8 ins. diam., with healed blazes on the E. and W. faces; from which the one remaining original bearing tree, as follows:

A sawed fir stump, 21 ins. diam., bears N.  $80^{\circ}$  W., 14 lks. dist., with illegible scribe marks visible on a partially opened blaze.

And new bearing trees and reference monument

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base to top, for a reference monument, bears S.  $72^{\circ}$  E.,  $17\frac{1}{4}$  lks. dist., with brass cap marked T28S R4W  $\frac{1}{4}$  S3 RM 1958, with an arrow pointing to the corner.

A cedar, 13 ins. diam., bears N.  $71^{\circ}$  W., 49 lks. dist., marked  $\frac{1}{4}$  S4 BT.

The corner tree has been used as a fence corner with fences extending North and West.

N.  $1^{\circ} 23'$  W., beginning new Measurement.

Ascend 71 ft. over S. slope, through logged area, along fence line.

6.50 Ridge, bears N.  $70^{\circ}$  E. and S.  $60^{\circ}$  W.; Desc. 46 ft. over NW. slope.