

County Surveyor's Record, Douglas County, Oregon

28

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

$$E \frac{1}{16} \frac{S \ 28}{S \ 33}$$

1958

from which new bearing trees:

A hemlock, 9 ins. diam., bears N. $37\frac{1}{4}^{\circ}$ E., 25 lks. dist., marked E $\frac{1}{16}$ S 28 BT.

A fir, 14 ins. diam., bears S. 10° E., 48 lks. dist., marked E $\frac{1}{16}$ S33 BT.

Reset iron pipe alongside iron post.

Ascend 649 ft. over general E. slope, through heavy timber and dense undergrowth.

41.28

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, perpetuated and recorded by G.G. Stewart, D.C.S., in 1922, at recorder bearing and distance from the remains of the original bearing trees; which no longer exist, monumented with an iron pipe, 1 in. diam., firmly set, 8 ins. above ground; from which bearing trees by Stewart in 1922:

A fir, 51 ins. diam., bears N. 30° E., 21 lks. dist., with scribe marks $\frac{1}{4}$ S CS BT. visible on bark blaze.

A white fir, 33 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ W., 111 lks. dist., with healed blaze.

and local bearing tree of which I have no record.

A cedar, 7 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ E., 32 lks. dist., with scribe marks $\frac{1}{4}$ S28 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T28S R4W

$$\frac{1}{4} \frac{S \ 28}{S \ 33}$$

1958

Reset iron pipe alongside iron post.

S. $88^{\circ} 28'$ W., beginning new measurement.

Ascend 205 ft. over SE. slope, through heavy timber and dense undergrowth.

6.03

Ridge, divide between North Myrtle Creek drainage and Frozen Creek drainage, bears NE. and SW.; descend 651 ft. over NW. slope changing to W. slope.

17.41

Leave timber, enter open rocky area, edge bears NW. and SE.

20.96

Leave rocky area, enter heavy timber, edge bears NE. and SW.

26.85

Four strand barbed wire fence, bears NE. and SW.

26.94

Ravine, drains NW.; descend 157 ft. over general W. slope.

37.73

The cor. of secs. 28, 29, 32 and 33, perpetuated and recorded by J. H. Markham, in 1949, at record bearing and distance from the original bearing trees, monumented with a wooden post 3x3 ins. cross section, firmly set, 30 ins. above ground and remonumented