

County Surveyor's Record, Douglas County, Oregon

32

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

blackberry, fern, hazel, arrowwood, salal, Oregon grape and manzanita.

From the cor. of secs. 15, 16, 21 and 22.

N. 88° 06' W., bet secs. 16 and 21.

Ascend 270 ft. over SE. slope, through heavy timber and dense undergrowth.

8.05 Spur, slopes N. 30° E.; descend 18 ft. over NW. slope.

10.40 Ravine, drains NE.; ascend 222 ft. over NE. slope.

19.30 Ridge, bears N. and S.; descend 232 ft. over SW. slope.

34.65 Foot of descent, slopes S.; ascend 32 ft. over SE. slope.

38.60 Spur, slopes S.; descend 13 ft. over W. slope.

39.70 The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, determined at record distance from the two original bearing trees, as follows:

A madrone, 26 ins. diam., bears N. 25° E., 60 lks. dist., with illegible scribe marks visible on a partially opened blaze.
(Record bearing N. 10° E.)

A madrone, 31 ins. diam., bears S. 18° W., 48 lks. dist., with faint scribe marks visible on a partially opened blaze.
(Record bearing S. 20° W.)

At the corner point.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T28S R4W

$$\frac{1}{4} \begin{array}{l} S 16 \\ S 21 \end{array}$$

1958

from which

A fir, 13 ins. diam., bears N. 25° E., $27\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S16 BT.

A white fir, 8 ins. diam., bears S. 13° W., 65 lks. dist., marked $\frac{1}{4}$ S21 BT.

N. 89° 39' W., beginning new measurement.

Descend 198 ft. over SW. slope, through heavy timber and dense undergrowth.

17.65 Creek, 8 lks. wide, course S. 20° E.; ascend 359 ft. over E. slope changing to SE. slope.

36.15 Spring branch, 1 lk. wide, course S. 70° E.; ascend 96 ft. over NE. slope.

38.88 The cor. of secs. 16, 17, 20 and 21, perpetuated and recorded by J. W. Byron, D.C.S., in 1957, at record bearing and distance from the only remaining bearing tree; monumented with an iron post, 1 in. diam., firmly set, 12 ins. above ground, with brass cap marked

County Surveyors

T28S R4W

SEC S 17 | S 16

COR S 20 | S 21

1957
Office