

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS

from which the original bearing tree:

A fir, 42 ins. diam., bears N. 28° W., 60 lks. dist., bark scribed S17 T28S R4W BT.

and a marked tree of which I have no record:

A fir, 39 ins. diam., bears N. 20° W., 25 lks. dist., bark scribed S21 on E., S16 on N., and illegible scribe marks on the S. face.

and locally established bearing tree:

A cedar, 16 ins. diam., bears N. 54° E., 12½ lks. dist., marked T28S R4W S16 CS BT.

A madrone, 16 ins. diam., bears S. 55½° E., 32½ lks. dist., marked T28S R4W S. 21 CS BT.

A fir, 20 ins. diam., bears S. 35° W., 30 lks. dist., bark scribed T28S R4W S20 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T28S R4W  
S 17 | S 16  
S 20 | S 21  
1958

Deposit County Surveyor's iron pipe alongside iron post.

Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, yew, maple and madrone; undergrowth, vinemaple, fern, Oregon grape, salal, hazel, dogwood, oceanspray, chinquapin and poison oak.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 32' W., bet. secs. 9 and 16,

Descend 171 ft. over SW. slope, through scattering timber, along S. edge of logged area.

11.40 Creek, 3 lks. wide, course S. 20° E.; ascend 100 ft. over SE. slope.

15.15 Spur, slopes S. 30° E.; descend 7 ft. over along SW. slope.

17.75- Ravine, drains S. 30° E.; ascend 250 ft. over SE. slope.

24.15 Dirt access road, 20 lks. wide, bears N. curving to E. and S. curving to W.

27.10 Spur, slopes S. 20° E.; Ascend 20 ft. along S. slope.

32.15 Ravine, drains S. 30° E.; ascend 205 ft. over SE. slope.

35.70 Abandoned access road, 10 lks. wide, bears N. curving to E. and S. curving to W.

38.74 The ¼ sec. cor. of secs. 9 and 16, determined at record distance from the remains of the original bearing trees, as follows:

A sawed and burned fir stump, 72 ins. diam., bears N. 28½° E., 23 lks. dist., with faint and illegible scribe marks visible. (Record bearing N. 30° E.)

A broken-off fir snag, 60 ins. diam., bears S. 54° W., 45 lks.