

County Surveyor's Record, Douglas County, Oregon

34

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S. R. 4 W.

CHAINS

dist., with axe marks visible. (Record bearing S. 45° W.)

at the corner point

Set an iron post, 28 ins. long, 2½ ins diam., 24 ins. in the ground, with brass cap marked

T28S R4W

 $\frac{1}{4}$ S 9
S 16

1958

from which

A white fir, 8 ins. diam., bears N. 32° W., 35 ¾ lks. dist., marked $\frac{1}{4}$ S9 BT.A white fir, 15 ins. diam., bears S. 43° 45' W., 96 lks. dist., marked $\frac{1}{4}$ S16 BT.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 29' W., bet. secs. 4 and 9.

Descend 143 ft. along N. slope.

7.80 Foot of descent, slopes N.; ascend 20 ft. over NE. slope.

9.50 Spur, slopes N.; descend 371 ft. over NW. slope.

22.35 Creek, 4 lks. wide, course N. 10° W., ascend 37 ft. over NE. slope.

23.75 Top of ascent, slopes N.; descend 113 ft. over NW. slope.

26.00 Creek, 8 ins. wide,, course S. 50° W., 62 ft. along S. slope.

33.00 Top of ascent, slopes SW.; descend 35 ft. over SW. slope.

35.30 Ravine, drains S.; ascend 92 ft. over SE. slope.

39.07 The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, determined at record distance from the two original bearing trees, as follows:A fir, 34 ins. diam., bears N. 29° W., 42 lks. dist., bark scribed $\frac{1}{4}$ S BT. (Record bearing N. 28° W.)A fir, 50 ins. diam., bears S. 27½° W., 27 lks. dist., bark scribed $\frac{1}{4}$ S BT. (Record bearing S. 25° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T28S R4W

 $\frac{1}{4}$ S 4
S 9

1958

from which

A fir, 21 ins. diam., bears S. 5° W., 64 lks. dist., marked $\frac{1}{4}$ S9 BT.

N. 89° 58' W., beginning new measurement.

Ascend 26 ft. along S. slope, through heavy timber and dense undergrowth.