

County Surveyor's Record, Douglas County, Oregon

36

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS 21.15	Creek, 5 lks. wide, course S.; ascend 218 ft. over SE. slope changing to E. slope.
31.45	Spur ridge, bears N. and S.; descend 42 ft. over SW. slope.
34.90	Ravine, drains S. 30° W.; ascend 37 ft. over SE. slope.
38.75	Top of ascent, slopes S.; descend 7 ft. over SW. slope.
39.62	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
	T28S R4W $\frac{1}{4}$ S 17 $\frac{1}{4}$ S 20 1958
	from which A cedar, 7 ins. diam., bears N. 16 $\frac{1}{2}$ ° W., 36 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S17 BT. A fir, 10 ins. diam., bears S. 16 $\frac{1}{2}$ ° E., 54 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S20 BT. Corner falls on top of a small spur, slopes SW. Descend 322 ft. over NW. slope.
51.65	Creek, 3 lks. wide, course S. 60° W.; descend 18 ft. along S. slope.
53.00	Creek, 3 lks. wide, course S.; ascend 321 ft. over SE. slope.
61.40	Spur, slopes S.; descend 190 ft. over SW. slope.
73.15	Dry creek bed, 4 lks. wide, course S. 30° E.; ascend 270 ft. over E. slope.
79.24	The cor. of secs. 17, 18, 19 and 20, determined at the intersection of the bearings from the faces of four bearing trees, of which I have no record. The scribing on these trees bear the same characteristics as those found on positively identified original cors. and by counting the growth rings on one of the most scribed trees gives the proper date for the original survey. The bearing trees found are as follows: A fir, 13 ins. diam., bears N. 34 $\frac{1}{2}$ ° E., 7 lks. dist., with S17 T28S R4W BT. visible on an opened blaze. A fir, 23 ins. diam., bears S. 56 $\frac{1}{4}$ ° E., 15 lks. dist., with illegible scribe marks visible on opened blaze. A fir, 11 ins. diam., bears S. 13° W., 14 $\frac{1}{2}$ lks. dist., with an illegible bark scribe. A fir, 35 ins. diam., bears N. 41° W., 18 $\frac{1}{4}$ lks. dist., bark scribed S18 T28S R4W BT. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked