

County Surveyor's Record, Douglas County, Oregon

2

Dependent Resurvey of Portion of the S. Bdy., T. 25 S., R. 4 W.

CHAINS

A black oak, 11 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ E., 158 lks. dist., marked T25S R4W S36 BT.

An alder, 13 ins. diam., bears S. $60\frac{1}{4}^{\circ}$ E., 401 lks. dist., marked T26S R4W S1 BT.

A madrone, 6 ins. diam., bears S. 85° W., 64 lks. dist., marked T26S R4W S2 BT.

A madrone, 7 ins. diam., bears N. $38^{\circ} 45'$ W., 86 lks. dist., marked T25S R4W S35 BT.

From this point the cor. of Tps. 25 and 26 S., Rs. 3 and 4 W., bears N. $89^{\circ} 38'$ E., 78.68 chs. dist., monumented with an iron post, 3 ft. long, 3 ins. diam., 8 ins. above ground, firmly set, with brass cap marked

T25S	
R4W	R 3 W
S 36	S 31
S 1	S 6
T26S	
1943	

from which previously marked bearing trees,

A cedar, 27 ins. diam., bears N. $14^{\circ} 45'$ E., 59 lks. dist., with scribe marks visible on partly healed blaze. (Price B.T.)

A sawed fir stump, 17 ins. diam., bears S. 37° E., 20 lks. dist., scribe marks visible on partly healed blaze. (Price B.T.)

A cedar, 28 ins. diam., bears S. $87^{\circ} 45'$ W., 146 lks. dist., with scribe marks visible on partly healed blaze. (Price B.T.)

A cedar snag, 10 ins. diam., bears N. $31^{\circ} 45'$ W., 35 lks. dist., with scribe marks visible on partly healed blaze. (County surveyor bearing tree notes by Price in 1943.)

and a new bearing tree:

A cedar, 15 ins. diam., bears S. $29^{\circ} 45'$ E., 246 lks. dist., marked T26S R3W S6 BT.

There is no suitable live tree convenient in sec. 36. The township corner is located at a corner of fences extending S. and W.

S. $89^{\circ} 38'$ W., between secs. 2 and 35, marking and blazing the true line.

Ascend 443 ft. over SE. slope through partially logged area with scattering timber and reproduction.

18.55 Ridge, bears N. 10° E. and S. 10° W.; descend 329 ft. over W. Slope.

23.98 Abandoned logging road, 10 lks. wide, bears N. and S.

26.90 Creek, 3 lks. wide, course S.; ascend 324 ft. over SE. slope.

38.68 Spur, slopes S.; continue along S. slope.

39.34 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W	
$\frac{1}{4}$	S 35
	S 2
T26S	
1957	

from which