

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the E. Bdy., T. 25 S., R. 4 W.

CHAINS  
40.02

The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

N.  $0^{\circ} 20'$  W., beginning new measurement.

Ascend 12 ft. over broken SE. slope.

- 9.26 Spur, slopes E.; descend 61 ft. over NE. slope.
- 16.55 Foot of descent, slopes E., and skid road, 20 lks. wide, bears NW. and SE.; ascend 78 ft. over SE. slope.
- 25.13 Spur, slopes E.; descend 82 ft. over NE. slope.
- 33.18 Foot of descent, slopes E.; ascend 39 ft. over SE. slope.
- 38.85 Woven-wire fence, bears N.  $10^{\circ}$  E. and S.  $10^{\circ}$  W.
- 40.35 The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., 2 ins. above ground, firmly set, with brass cap marked

T25S	
R4W	R 3W
S 25	S 30
S 36	S 31
1943	

from which

A cedar, 10 ins. diam., bears N.  $13\frac{1}{2}^{\circ}$  E., 79 lks. dist., with scribe marks T25S R3W S30 BT. visible on open blaze.

A cedar, 13 ins. diam., bears S.  $10\frac{1}{2}^{\circ}$  E., 46 lks. dist., with a healed blaze.

and new bearing trees:

A cedar, 16 ins. diam., bears S.  $15^{\circ}$  E., 161 lks. dist., marked T25S R3W S31 BT.

A cedar, 18 ins. diam., bears N.  $7^{\circ}$  W., 160 lks. dist., marked T25S R4W S25 BT.

Land, mountainous. Soil, sandy loam and rocky loam. Timber, fir, hemlock, cedar, pine, oak, maple, madrone, alder and dogwood; undergrowth, vinemaple, salal, hazel and fir reproduction.

N.  $0^{\circ} 10'$  W., between secs. 25 and 30.

Ascend 227 ft. over SE. slope, through heavy timber and dense undergrowth.

- 1.30 Woven-wire fence, bears NW. and SE.
- 16.23 Dirt logging road, 25 lks. wide, bears NE. and SW.
- 17.23 Spur, slopes SW.; descend 34 ft. over NW. slope.
- 24.68 Foot of descent, slopes W.; ascend 74 ft. over SW. slope.
- 28.30 Abandoned skid road, 20 lks. wide, bears NW. and SE.
- 30.13 Spur, slopes NW.; descend 188 ft. over NE. slope.
- 38.07 Foot of descent, slopes W.; ascend 33 ft. along W. slope.
- 39.70 Abandoned skid road, 20 lks. wide, bears N.  $30^{\circ}$  W. and S.  $30^{\circ}$  E.
- 40.27 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, marked and witnessed