

County Surveyor's Record, Douglas County, Oregon

5

Dependent Resurvey of Portion of the E. Bdy., T. 25 S., R. 4 W.

CHAINS

as described in the official record.

N. 0° 35' W., beginning new measurement.

Descend 38 ft. over NW. slope.

11.77 Spring branch, 5 lks. wide, course W.; ascend 17 ft. over SW. slope.

12.30 Spur, slopes W.; descend 10 ft. over NW. slope.

13.07 Creek, 8 lks. wide, course SW.; ascend 406 ft. over SE. slope.

40.06 The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous. Soil, sandy loam and rocky loam. Timber, fir, hemlock, cedar, yew, maple, alder, dogwood, madrone, and oak; Undergrowth, vinemaple, salal, hazel, willow, salmonberry and poison oak.

From the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2 ins. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record.

N. 0° 42' E., between secs, 13 and 18.

Ascend 131 ft. over SE. slope, through heavy timber and dense undergrowth.

6.10 Spur, slopes S. 70° W.; descend 47 ft. over NW. slope.

9.60 Foot of descent, slopes W.; ascend 149 ft. over SW. slope.

20.01 Point for the S. 1/16 sec. cor., of secs. 13 and 18.

Set an iron post, 28 ins. long, 2 1/8 ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{S } 1/16 \\ | \\ \text{S } 13 \text{ } | \text{ } \text{S } 18 \\ | \\ 1958 \end{array}$$

from which

A fir, 10 ins. diam., bears N. 64 1/2° E., 43 lks. dist., marked S 1/16 S18 BT.

A fir, 8 ins. diam., bears S. 22° 45' W., 13 lks. dist., marked S 1/16 S13 BT.

21.60 Spur, slopes W.; descend 88 ft. over NE. slope.

23.17 Abandoned skid road, 20 lks. wide, bears NW. and SE.

27.10 Foot of descent, slopes E.; ascend 64 ft. over SE. slope.

32.50 Spur, slopes E., also abandoned skid road, 20 lks. wide, bears E. and W.; descend 195 ft. over NE. slope.

40.02 The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., 6 ins. above ground, firmly set, marked and witnessed as described in the official record.

N. 2° 04' E., beginning new measurement.

Descend 139 ft. over NE. slope, changing to E. slope.