

County Surveyor's Record, Douglas County, Oregon

7

. Dependent Resurvey of Portion of the W. Bdy., T. 25 S., R. 4 W.

CHAINS

- 5.73 Dry branch, 1 lk. wide, course SW.; ascend 174 ft. over S. slope changing to SW. slope.
- 16.41 Spur, slopes W.; descend 91 ft. over NW. slope.
- 19.34 Woven-wire fence, bears E. and W.; also fence corner bears W. 21 lks. dist., with fences extending N., S., E., and W.; enter logged area.
- 19.855 Point for the S. 1/16 sec. cor. of secs. 19 and 24.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins diam., 26 ins. in the ground, with brass cap marked
- S 1/16
S 24 | S 19
1957
- from which
- A fir, 18 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ E., 54 lks. dist., marked S 1/16 S19 BT.
- A fir, 14 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 66 lks. dist., marked S 1/16 S24 BT.
- Descend 35 ft. over NW. slope, near a fence, through logged area.
- 22.27 Ravine, course W.; ascend 16 ft. over SW. slope.
- 24.37 Spur, slopes NW.; descend 267 ft. over N. slope.
- 39.71 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, determined at record bearing and distance from the only remaining original bearing tree,
A white oak, 22 ins. diam., bears S. 19° E., 98 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.
- At the corner point
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
- T25S
R5W | R4W
S 24 | S 19
1957
- from which
- A fir, 11 ins. diam., bears S. 81° E., 67 lks. dist., marked $\frac{1}{4}$ S19 BT.
- A fir, 10 ins. diam., bears S. $70\frac{1}{4}^{\circ}$ W., $30\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S24 BT.
- The corner falls at the foot of N. slope and by a fence extending N. and S.
-
- N. $0^{\circ} 29'$ E., beginning new measurement.
- Descend 35 ft. along a fence over valley bottom through scattering timber.
- 0.67 SW. corner of open field, edges bear N. and E.; also from this point a spring bears W., 90 lks. dist.