

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of the W. Bdy., T. 25 S., R. 4 W.

CHAINS

- 2.46 Corner of fences extending N. 20° W., S., and W.; thence across open fields.
- 5.82 Wire fence, bears N. 35° W. and S. 35° E.
- 9.44 Sutherlin Creek, 10 lks. wide, course NW.; ascend 36 ft. over S. slope, on bottom land.
- 18.65 Corner of fences at edge of fields extending N., S. 75° E., and S. 20° W.; thence along fence through scrub oak.
- 19.34 Top of ascent, slopes W.; descend 32 ft. over NW. slope changing to level valley bottom.
- 19.99 Corner of wire fences, extending S., E., and W.
- 21.17 Leave scrub oak, edge bears E. and SW.; thence across open fields.
- 31.42 Abandoned irrigation ditch, bears N. 20° E. curving to N. 40° E. and S. 20° W.
- 40.33 The cor. of secs. 13, 18, 19 and 24, determined at record bearing and distance from the remaining original bearing tree in field,

An uprooted and decayed black oak, 25 ins. diam., bears N. 7° 45' W., 925 lks. dist. I opened a badly decayed blaze and found 5W T25S S13 on over growth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. below the surface of the ground, with brass cap marked

T25S	
R5W	R4W
S 13	S 18
S 24	S 19
1957	

from which

An ash, 12 ins. diam., bears N. 6½° E., 427 lks. dist., marked T25S R4W S 18 BT.

An ash, 11 ins. diam., bears S. 37° E., 591 lks. dist., marked T25S R4W S19 BT.

An ash, 7 ins. diam., bears S. 22° W., 523 lks. dist., marked T25S R5W S 24 BT.

An ash, 10 ins. diam., bears N. 67¼° W., 313 lks. dist., marked T25S R5W S13 BT.

Land, N. half mile open valley bottom; S. half mile mountainous. Soil, N. half mile loam; S. half mile clay and loam. Timber, fir, cedar, white and black oak, maple, madrone and ash; undergrowth, vinemaple, hazel, scrub oak, slal and huckleberry.

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.
(Restoring the 1855 Survey by Gordon and Gardner, and the 1871 Survey by W. H. Byars)

From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of Tp.

N. 3° 22' W., between secs. 35 and 36, marking and blazing true line.

Ascend 233 ft. over broken SE. slope, through burned-off and logged area.