


County Surveyor's Record, Douglas County, Oregon

9

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- 2.59 Woven-wire fence bears E. and W.
- 20.52 Spring branch, 3 lks. wide, course SE.; ascend 183 ft. over S. slope, changing to SE. slope.
- 28.90 Spur, slopes E.; descend 223 ft. over NE. slope.
- 39.43 Point for the $\frac{1}{4}$ sec. cor., of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked



from which


A fir, 8 ins. diam., bears N. 82° E., 95 lks. dist., marked $\frac{1}{4}$ S36 BT.

A fir, 40 ins. diam., bears N. 61° W., 41 lks. dist., marked $\frac{1}{4}$ S35 BT.

Descend 57 ft. over NE. slope.

- 40.50 Creek, 10 lks. wide, course E.; ascend 541 ft. over SW. slope changing to S. slope.
- 62.50 Spur, slopes SE.; descend 108 ft. over NE. slope.
- 68.80 Spring branch, 2 lks. wide, course E.; asc. 102 ft. over SE. slope.
- 73.68 Spur, slopes E.; also abandoned skid road, 20 lks. wide, bears E. and W.; descend 164 ft. over NE. slope.
- 78.86 The cor. of secs. 25, 26, 35 and 36, perpetuated by the county surveyor with an iron pipe, 1 in. diam., protruding 12 ins. above ground, firmly set with brass cap marked

COUNTY SURVEYORS



from which the remains of the original bearing trees:

A fir, 55 ins. diam., bears N. 70° E., 30 lks. dist., rescribed S25 CS on bark by county surveyor.

A fragmentary piece of cedar stump, bears S. $37\frac{1}{2}^{\circ}$ W., 16 lks. dist., marked T25S S35 BT. (Record bearing S. 35° W.)

and trees marked by the county surveyor,

A cedar, 18 ins. diam., bears S. $9\frac{1}{4}^{\circ}$ E., 65 lks. dist., marked S36 CS on partially healed blaze.

A cedar, 18 ins. diam., bears S. $59\frac{1}{4}^{\circ}$ W., $30\frac{1}{2}$ lks. dist., marked T25S S35 CS on partially healed blaze.

A cedar, 15 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 119 lks. dist., marked T25S S26 R4W CS BT on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground,