

County Surveyor's Record, Douglas County, Oregon

15

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A dogwood, 4 ins. diam., bears N. $34^{\circ} 45'$ E., 7 lks. dist., with scribe marks S13 CS BT visible on partially healed blaze.

A cedar, 16 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ W., 25 lks. dist., with scribe marks S23 S BT. visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{r} T25S R4W \\ \hline S 14 | S 13 \\ S 23 | S 24 \\ 1957 \end{array}$$

from which

A cedar, 13 ins. diam., bears N. $30\frac{1}{4}^{\circ}$ E., 64 lks. dist., marked T25S R4W S13 BT.

A fir, 6 ins. diam., bears S. $41\frac{1}{4}^{\circ}$ E., 56 lks. dist., marked T25S R4W S24 BT.

A cedar, 15 ins. diam., bears S. 47° W., 42 lks. dist., marked T25S R4W S23 BT.

A cedar, 13 ins. diam., bears N. $25^{\circ} 45'$ W., 65 lks. dist., marked T25S R4W S14 BT.

Reset the cedar post alongside the iron post.

Land, mountainous. Soil, stony clay and loam. Timber, fir, cedar, hemlock, maple, scattered dogwood and madrone; undergrowth, salal, vinemaple, hazel and poison oak.

From the cor. of secs. 13, 18, 19 and 24 on E. bdy. of the Tp.

S. $87^{\circ} 33'$ W., bet. secs. 13 and 24.

Descend 236 ft. over SW. slope along N. edge of logged area, through scattering timber and dense undergrowth.

6.80 Ravine, course S.; ascend 150 ft. over SE. slope.

18.43 Point for the E 1/16 sec. cor. of secs. 13 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{r} E 1/16 \quad S 13 \\ \hline S 24 \\ 1957 \end{array}$$

from which

A cedar, 21 ins. diam., bears N. 25° E., 65 lks. dist., marked E 1/16 S13 BT.

A cedar, 18 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ E., 83 lks. dist., marked E 1/16 S24 BT.

The corner falls on a spur, sloping S. Descend 358 ft. over SW. slope.

36.19 Main access road, bears NW. and SE., 30 lks. wide.

36.86 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{r} T25S R4W \\ \hline \frac{1}{4} S 13 \\ S 24 \\ 1957 \end{array}$$