

County Surveyor's Record, Douglas County, Oregon

18

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

S. 89° 43' W. bet. secs. 12 and 13.

Descend 42 ft. over SW. slope, through heavy timber and dense undergrowth.

0.13 Woven wire fence, bears N. and S.

3.38 Spring branch, 2 lks. wide, course S. 85° W.; Descend 100 ft. over SW. slope.

22.21 Slide Creek, 5 lks. wide, course N.; ascend 164 ft. over E. slope.

23.85 Gravelled and maintained road, 30 lks. wide, bears N. 20° W. and S. 20° E.

32.41 Spur, slopes N.; descend 170 ft. over W. slope changing to NW. slope.

41.90 The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, perpetuated by the county surveyor with an iron pipe 1 in. diam., protruding 6 ins. above ground, with brass cap marked

COUNTY SURVEYORS

T25S R4W

 $\frac{1}{4}$ S 12 $\frac{1}{4}$ S 13

1956

OFFICE

from which the remaining original bearing tree:

A fir, 40 ins. diam., bears N. 16° E., 40 lks. dist., bark scribed $\frac{1}{4}$ S12 BT over a healed blaze.

and a tree marked by the county surveyor,

A fir, 18 ins. diam., bears S. 17° W., 81 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S13 CS BT. visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ diam., 6 ins. below the surface of the road, with brass cap marked

T25S R4W

 $\frac{1}{4}$ S 12 $\frac{1}{4}$ S 13

1957

from which

A fir, 40 ins. diam., bears N. 71° E., 100 lks. dist., marked $\frac{1}{4}$ S12 BT.A cedar, 17 ins. diam., bears S. 73 $\frac{1}{2}$ ° W., 98 lks. dist., marked $\frac{1}{4}$ S13 BT.

Reset the iron pipe alongside the iron post.

The corner falls in a gravelled and maintained road, 25 lks. wide, bears N. 55° E. curving to N. and S. 55° W. curving to W.

S. 87° 35' W., beginning new measurement.

Descend 17 ft. over NW. slope.

0.27 Woven wire fence, bears NE. and SW.

1.96 Gassy Creek, 5 lks. wide, course NE.; ascend 423 ft. over SE. slope changing to steep E. slope.