

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- 10.23 Corner of woven wire fences, extending N., E. and W.
- 17.63 Corner of fences, extending E. and S.
- 19.20 Abandoned skid road, 20 lks. wide, bears N. and S.
- 29.62 Spur, slopes S.; also dirt access road, 20 lks. wide, bears N. and S. descend 218 ft. over SW. slope.
- 30.77 Abandoned skid road, 20 lks. wide, bears N. 10° W. and S. 10° E.
- 34.46 Skid road, 20 lks. wide, bears N. and S.
- 36.60 Woven wire fence, bears N. and S.
- 36.62 The corner of secs. 11, 12, 13 and 14.

Land, hilly. Soil, clay and loam. Timber, fir, cedar, hemlock, maple, and scattering pine; undergrowth, hazel, salal, scattering manzanita, poison oak and ocean spray.

From the corner of secs. 2, 3, 34 and 35 on S. Bdy. of the Tp.

N. 1° 01' E., bet. secs. 34 and 35.

Descend 49 ft. over NW. slope.; through heavy timber and dense undergrowth.

- 3.24 Head of ravine, course N. 60° W.; ascend 70 ft. over SW. slope.
- 7.92 Spur, slopes W.; descend 256 ft. over NW. slope.
- 15.73 Ravine, course W.; ascend 30 ft. over SW. slope.
- 18.49 Spur, slopes W.; descend 67 ft. over NW. slope.
- 21.95 Ravine, course W.; ascend 60 ft. over SW. slope.
- 25.02 Spur, slopes W.; descend 304 ft. over NW. slope.
- 34.48 Creek, 3 lks. wide, course N. 60° W.; ascend 100 ft. over SW. slope.
- 39.99 The  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, perpetuated, at record bearing and distance from the only original bearing tree, by an iron post 1 in. diam., 8 ins. above ground, firmly set, with brass cap marked

DOUGLAS COUNTY  
T25S R4W

$\frac{1}{4}$  S 34 | S 35

1955  
SURVEYOR'S OFFICE

from which the original bearing tree,

A split cedar snag, 23 ins. diam., bears N. 78° E., 23 lks. dist. with scribe marks  $\frac{1}{4}$  S visible on open blaze; tree has been re-scribed  $\frac{1}{4}$  S35.

newly established bearing trees by county surveyor,

A yew, 13 ins. diam., bears N. 10° E., 67 lks. dist., marked  $\frac{1}{4}$  S35 CS BT on an unhealed blaze.

A cedar, 12 ins. diam., bears N. 53° W., 100 lks. dist., marked  $\frac{1}{4}$  S34 CS BT. on an unhealed blaze.