

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A madrone, 8 ins. diam., bears S.  $35\frac{1}{4}^\circ$  E., 176 lks. dist., marked T25S R4W S35 BT.

A fir, 38 ins. diam., bears S.  $50^\circ$  W., 468 lks. dist., marked T25S R4W S34 BT.

A fir, 48 ins. diam., bears W.; 406 lks. dist., marked T25S R4W S34 BT.

Deposit county surveyor's post alongside iron post.

Land, mountainous. Soil, loam and stony clay. Timber, fir, cedar, yew, maple, madrone, and hemlock; undergrowth, hazel, arrowwood, poison oak, salal, and reproduction.

From the cor. of secs. 25, 26, 35 and 36.

N.  $89^\circ 55'$  W., between secs. 26 and 35.

Ascend 230 ft. over NE. slope, through heavy timber and light undergrowth.

6.36 Abandoned logging road, 15 lks. wide, bears N.  $30^\circ$  W. and S.  $30^\circ$  E.

9.29 Ravine, course N.  $30^\circ$  E.; ascend 151 ft. over E. slope.

13.46 Spur ridge, bears N.  $15^\circ$  W. and S.  $20^\circ$  E.; also enter logged area, edge bears N. and S.; descend 223 ft. over W. slope changing to SW. slope.

19.75 Abandoned logging road, 15 lks. wide, bears NW. and SE.

21.09 Foot of descent, slopes S.; ascend 36ft. over SE. slope.

23.84 Top of ascent, slopes S.; descend 53 ft. over SW. slope.

24.73 Abandoned logging road, 15 lks. wide, bears NW. and E. curving to NE.

27.32 Foot of descent, slopes S.; ascend 186 ft. over SE. slope.

37.07 The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, restored by the county surveyor by single proportionate measurement in 1955 and monumented with an iron post, 1 in. diam., 12 ins. above ground, firmly set, with brass cap marked

COUNTY SURVEYORS

T25S R4W

$\frac{1}{4}$  S 26

$\frac{1}{4}$  S 35

1955

OFFICE

from which county surveyor's bearing trees

A cedar, 10 ins. diam., bears N.  $29^\circ 45'$  E., 386 lks. dist., marked  $\frac{1}{4}$  S26 CS BT on an unhealed blaze.

A cedar, 10 ins. diam., bears S.  $28\frac{1}{4}^\circ$  E., 93 lks. dist., marked  $\frac{1}{4}$  S35 CS BT on an unhealed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W

$\frac{1}{4}$  S 26

$\frac{1}{4}$  S 35

1957

from which