

County Surveyor's Record, Douglas County, Oregon

22

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A cedar, 13 ins. diam., bears N. $39\frac{1}{2}^{\circ}$ E., 508 lks. dist., marked $\frac{1}{4}$ S26 BT.

A cedar, 12 ins. diam., bears S. 10° E., $178\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S35 BT.

Deposit county surveyor's corner alongside the iron post.

N. $89^{\circ} 55'$ W., beginning new measurement.

Ascend 71 ft. over E. slope.

- 2.75 Spring branch, $\frac{1}{2}$ lk. wide, course SE.; ascend 261 ft. over NE. slope changing to E. slope.
- 9.52 Graded logging road, 15 lks. wide, bears N. 10° E. and S.; also enter burned area with scattering timber and heavy undergrowth, edge bears N. and S.
- 10.55 Main ridge between Cooper Creek and Huntley Creek, bears N. 10° E. and S.; descend 483 ft. over W. slope changing to NW. slope.
- 21.40 Spring branch, 1 lk. wide, course W.; descend 60 ft. over SW. slope.
- 27.04 Foot of descent, slopes S.; ascend 108 ft. over E. slope.
- 31.44 Spur, slopes SW.; descend 140 ft. over W. slope.
- 36.94 The corner of secs. 26, 27, 34 and 35.

Land, mountainous. Soil, stony clay. Timber, fir, cedar, madrone and maple; undergrowth, vinemaple, hazel, poison oak and salal.

N. $1^{\circ} 26'$ E., bet. secs. 26 and 27.

Descend 178 ft. over NW. slope, through burned area with scattering timber and dense undergrowth.

- 14.68 Ravine, course W.; ascend 20 ft. over SW. slope.
- 15.46 Spur, slopes W.; descend 35 ft. over NW. slope.
- 17.75 Creek, 2 lks. wide, course S. 20° W.; ascend 210 ft. over SW. slope, changing to W. slope.
- 29.44 Ravine, course SW.; ascend 202 ft. over SW. slope.
- 33.18 Leave burned area, continue along W. edge of logged area.
- 39.42 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, perpetuated at record bearing and distance from the original bearing trees with an iron post, 1 in. diam., 8 ins. above ground, firmly set, with a brass cap mkd.

DOUGLAS COUNTY

T25S R4W

 $\frac{1}{4}$ S 27 | 26

1955

SURVEYOR'S OFFICE

from which the original bearing trees

A cedar, 44 ins. diam., bears S. 10° E., 30 lks. dist., with scribe marks S visible on opened blaze.

An uprooted cedar, 30 ins. diam., bears S. 60° W., 43 lks. dist., no marks visible.