

County Surveyor's Record, Douglas County, Oregon

23

. Dependent Resurvey of Portion of Subdivisional Lines, T. 25S R. 4 W.

CHAINS


newly established bearing trees by county surveyor

A cedar, 18 ins. diam., bears N. 87° E., 61 lks. dist., with scribe marks $\frac{1}{4}$ S26 CS BT on unhealed blaze.

A fir, 8 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ W., $43\frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked.



from which

A fir, 9 ins. diam., bears S. $33\frac{1}{4}^{\circ}$ E., $44\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S26 BT.

A fir, 8 ins. diam., bears S. $21\frac{1}{4}^{\circ}$ W., 49 lks. dist., marked $\frac{1}{4}$ S27 BT.

Deposit county surveyor's corner alongside iron post.

N. $0^{\circ} 24'$ W., beginning new measurement.

Ascend 186 ft. over S. slope, through scattering timber and dense undergrowth, along W. edge of logged area.

- 9.75 Abandoned logging road, 20 lks. wide, bears N. 30° E. and S. 10° W.
- 13.06 Main ridge between Calapooya Creek and North Umpqua River drainage, bears SE. and W.; descend 268 ft. over N. slope.
- 13.64 Graded, dirt logging road, 25 lks. wide, bears S. 60° E. and W.
- 19.74 Spring branch, $\frac{1}{2}$ lk. wide, course N. 60° E.; ascend 24 ft. over SE. slope.
- 22.57 Top of ascent, slopes E.; descend 79 ft. over NE. slope.
- 27.39 Ravine, course N. 75° E.; ascend 5 ft. over SE. slope.
- 29.63 Top of ascent, slopes E.; descend 172 ft. over NE. slope changing to N. slope.
- 34.70 Ravine, course N. 70° E.; ascend 11 ft. over SE. slope.
- 36.08 Top of ascent, slopes E.; descend 78 ft. over NE. slope.
- 39.44 The cor. of secs. 22, 23, 26 and 27, determined at record bearing and distance from the only remaining original bearing tree,

A dead hemlock, 21 ins. diam., bears S. 50° W., 36 lks. dist., with scribe marks 7 5 BT visible on a partially opened and rotted blaze. (Record calls for a fir tree)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

