

County Surveyor's Record, Douglas County, Oregon

24

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

from which

A yew, 8 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ E., 66 lks. dist., marked T25S R4W S23 BT.

A cedar, 9 ins. diam., bears S. $50\frac{1}{4}^{\circ}$ E., 90 lks. dist., marked T25S R4W S26 BT.

A maple, 11 ins. diam., bears S. $45\frac{1}{4}^{\circ}$ W., 97 lks. dist., marked T25S R4W S27 BT.

A hemlock, 18 ins. diam., bears N. $53\frac{1}{2}^{\circ}$ W., 65 lks. dist., marked T25S R4W S22 BT.

Land, mountainous. Soil, stony clay. Timber, fir, cedar, hemlock, yew, maple, dogwood, and madrone; undergrowth, vinemaple, hazel, fern, poison oak, salal and small reproduction.

From the cor. of secs. 23, 24, 25 and 26.

N. $88^{\circ} 49'$ W., between secs. 23 and 26.

Descend 79 ft. over NW. slope, through scattering timber and dense fir reproduction.

- 2.12 Ravine, course N.; ascend 18 ft. over NE. slope.
- 3.59 Top of ascent slopes N.; descend 36 ft. over NW. slope.
- 6.13 Foot of descent, slopes N.; ascend 16 ft. over NE. slope.
- 7.23 Spur, slopes N. 30° W.; descend 154 ft. over W. slope.
- 11.22 Spring branch, 1 lk. wide, course NW.; descend 69 ft. along broken N. slope.
- 15.84 Ravine, course N.; ascend 361 ft. over NE. slope changing to E. slope.
- 19.91 Leave reproduction, enter logged area, edge bears NW. and SW.
- 26.96 Spur ridge, bears N. 15° E. and S. 15° W.; descend 179 ft. along broken N. slope.
- 38.32 Ravine, course N.; ascend 12 ft. over NE. slope.
- 38.89 Spur, slopes N.; descend 8 ft. over NW. slope.
- 39.27 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, perpetuated and recorded by local surveyor No. 2125, in 1951, from one of the original bearing trees, of which I find no evidence; monumented with a wooden stake, 4 ins. in cross section, firmly set, 2 ft. above ground.

from which locally established bearing trees,

A fir, 10 ins. diam., bears S. $57\frac{1}{2}^{\circ}$ E., 45 lks. dist., with scribe mark S visible on partially healed blaze and $\frac{1}{4}$ visible on bark.

A fir snag, 32 ins. diam., bears S. 71° W., 5 lks. dist., with $\frac{1}{4}$ axed on bark.

A cedar, 28 ins. diam., bears N. $12^{\circ} 45'$ W., 33 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked