

County Surveyor's Record, Douglas County, Oregon

27

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS
 50.42 Ravine, course W.; ascend 48 ft. over S. slope.
 53.37 Spur, slopes W.; descend 128 ft. over N. slope.
 60.30 Foot of descent, slopes W., enter logged area, edge bears E. and W.; ascend 70 ft. over broken SW. slope.
 63.17 Abandoned logging road, 10 lks. wide, bears N. and SW.
 68.24 Abandoned logging road, 10 lks. wide, bears NE. and S. 30° W.
 71.22 Top of ascent, slopes NW.; descend 92 ft. over N. slope changing to NW. slope.
 72.08 Abandoned logging road, 15 lks. wide, bears NE. and SW.
 77.21 Spring branch, 1 lk. wide, course W.; descend 23 ft. over NW. slope.
 81.10 Point for cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W	
S 15	S 14
S 22	S 23
1957	

from which

A fir, 8 ins. diam., bears N. $30\frac{1}{4}^\circ$ E., $79\frac{1}{2}$ lks. dist., marked T25S R4W S14 BT.

A fir, 8 ins. diam., bears S. $36\frac{1}{4}^\circ$ E., 25 lks. dist., marked T25S R4W S23 BT.

A fir, 13 ins. diam., bears S. $64^\circ 45'$ W., $115\frac{1}{2}$ lks. dist., marked T25S R4W S22 BT.

A fir, 8 ins. diam., bears N. $41\frac{1}{2}^\circ$ W., $104\frac{1}{2}$ lks. dist., marked T25S R4W S15 BT.

From this point the corner of secs. 2, 3, 10 and 11, bears N. $0^\circ 17'$ W., 161.94 chs. dist., determined at record bearing and distance from the only remaining original bearing tree:

A fir, 42 ins. diam., bears S. 85° E., 900 lks. dist., with illegible scribe marks on opened blaze.

and bearing trees marked by the county surveyor,

A fir 40 ins. diam., bears N. $8\frac{1}{2}^\circ$ E., 216 lks. dist., marked T25S R4W CS S 2.

A white oak, 12 ins. diam., bears S. $82\frac{1}{2}^\circ$ W., 300 lks. dist., marked with scribe marks R4W S10 CS visible on opened blaze.

A fir, 47 ins. diam., bears N. $59\frac{1}{2}^\circ$ W., 162 lks. dist., bark scribed T25S R4W S3 CS.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. below the surface of the ground in a field, with brass cap marked

T25S R4W	
S 3	S 2
S 10	S 11
1957	

from which