

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- A white oak, 19 ins. diam., bears N. 19° E., 153 lks. dist., marked T25S R4W S2 BT.
- A white oak, 17 ins. diam., bears S. 69° 45' E., 632 lks. dist., marked T25S R4W S11 BT.
- A white oak, 20 ins. diam., bears S. 12¼° W., 843 lks. dist., marked T25S R4W S10 BT.
- A white oak, 13 ins. diam., bears N. 82¼° W., 196 lks. dist., marked T25S R4W S3 BT.

From the same point the cor. of secs. 15, 16, 21 and 22, bears N. 88° 37' W., 80.61 chs. dist.; this cor. was rehabilitated and recorded by F. J. Cole, D.C.S., in 1914, from the remains of the original bearing trees, of which I find no evidence. The cor. point was determined at record bearing and distance from each of several bearing trees marked by Cole in 1914, as follows:

- A black oak, 15 ins. diam., bears N. 62½° E., 180 lks. dist., with a faint healed blaze.
- A white oak, 19 ins. diam., bears S. 31° W., 53 lks. dist., open faint blaze and uncover scribe marks S21 CS on face.
- A black oak, 22 ins. diam., bears N. 36° W., 128 lks. dist., with a faint healed blaze.

and an unrecorded local bearing tree,

- A white oak, 16 ins. diam., bears N. 60° 45' W., 52 lks. dist., open faint blaze and uncover scribe marks XRP on face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

Fd... M93-17

T25S R4W	
S 16	S 15
S 21	S 22
1957	

from which

- A black oak, 8 ins. diam., bears N. 79½° E., 147 lks. dist., marked T25S R4W S15 BT.
- A black oak, 11 ins. diam., bears S. 65¼° E., 69½ lks. dist., marked T25S R4W S22 BT.
- A black oak, 15 ins. diam., bears S. 33° W., 154 lks. dist., marked T25S R4W S21 BT.
- A black oak, 11 ins. diam., bears N. 32° W., 177 lks. dist., marked T25S R4W S16 BT.

Land, mountainous. Soil, clay and stony clay. Timber, fir, cedar, hemlock, yew, maple, madrone and oak; undergrowth, vinemaple, hazal, salal, fir reproduction and poison oak.

From the corner of secs. 13, 14, 23 and 24.

N. 89° 31' W., between secs. 14 and 23.

Descend 98 ft. over NW. slope, through heavy timber and dense undergrowth.

4.33 Foot of descent, slopes N.; ascend 44 ft. over NE. slope.

6.22 Spur, slopes N.; descend 46 ft. over NW. slope.