

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS 8.82	Foot of descent, slopes NE.; ascend 235 ft. over SE. slope.
18.45	Top of ascent, slopes NE.; descend 130 ft. over NW. slope.
24.00	Foot of descent, slopes N.; ascend 25 ft. over NE. slope.
27.37	Spur, slopes N.; 327 ft. over NW. slope, descent
30.45	Abandoned skid road, 20 lks. wide, bears N. and S.
40.00	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, perpetuated at record bearing and distance from the original bearing trees with an iron post, 1 in. diam., 10 ins. above ground, firmly set, with brass cap mkd.
	COUNTY SURVEYORS T25S R4W $\frac{1}{4}$ S $\frac{14}{23}$ 1956 OFFICE
	from which the original bearing trees
	A cedar stump, 36 ins. diam., bears N. 60° E., 8 lks. dist., with no scribe marks visible on opened blaze.
	A cedar, dead and down, 30 ins. diam., bears S. 10° W., 43 lks. dist., with a healed blaze.
	and locally established bearing tree
	A cedar, 17 ins. diam., bears S. 63 $\frac{1}{2}$ ° W., 127 lks. dist., marked $\frac{1}{4}$ S23 CS BT.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked
	T25S R4W $\frac{1}{4}$ S $\frac{14}{23}$ 1957
	from which
	A white fir, 15 ins. diam., bears North, 44 lks. dist., marked $\frac{1}{4}$ S14 BT.
	A white fir, 33 ins. diam., bears S. 56 $\frac{1}{2}$ ° W., 124 lks. dist., marked $\frac{1}{4}$ S23 BT.
	Deposit the county surveyor's post alongside the iron post.
	Corner falls on right bank of Norris Creek, 3 lks. wide, course N.
	<hr/> N. 88° 14' W.; beginning new Measurement.
	Ascend 525 ft. over SE. slope.
19.00	Spur, slopes N.; descend 36 ft. over NW. slope.
20.21	Point for W 1/16 sec. cor. of secs. 14 and 23.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked
	W 1/16 S $\frac{14}{23}$ 1957

SEE also  
C.S. 3658