

County Surveyor's Record, Douglas County, Oregon

30

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

from which

A fir, 10 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ W., 37 lks. dist., marked WL/16 S14 BT.

A cedar, 11 ins. diam., bears S. $63^{\circ} 45'$ E., $19\frac{1}{2}$ lks. dist., marked WL/16 S23 BT.

Descend 437 ft. over NW. slope.

31.00 Skid road, 20 lks. wide, bears NW. and SE.

40.42 The cor. of secs. 14, 15, 22 and 23.

Land, mountainous. Soil, stony clay. Timber, fir, cedar, hemlock, oak, maple and madrone; undergrowth, vinemaple, hazel, salal, fir reproduction and poison oak.

From the cor. of secs. 26, 27, 34 and 35.

N. $85^{\circ} 49'$ W., between secs. 27 and 34.

Descend 297 ft. over W. slope, through burned area.

8.21 Cooper Creek, 2 lks. wide, course S.; asc. 471 ft. over E. slope.

17.10 Skid road, 10 lks. wide, bears N. and SW.

23.06 Spur ridge, bears N. and S.; enter partially logged area; descend 364 ft. over SW. slope changing to W. slope.

29.06 Logging road, 15 lks. wide, bears N. 30° W. and SE.

33.85 Branch, $\frac{1}{2}$ lk. wide, course SW.; descend 6 ft. over W. slope.

34.97 Creek, 2 lks. wide, course S.; ascend 94 ft. over E. slope.

37.31 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, perpetuated with a cedar stake, 5 ins. sq. in cross section, 5 ft. above ground, firmly set. This corner was restored from the two original bearing trees by the county surveyor in 1955, one of which is still remaining, as follows:

A chopped cedar stump, 12 ins. diam., bears S. $55\frac{1}{4}^{\circ}$ W., 12 lks. dist., with BT visible on opened blaze and $\frac{1}{4}$ S visible on a portion of the tree lying alongside the stump.

Locally established bearing trees

A cedar, 33 ins. diam., bears N. $18\frac{1}{4}^{\circ}$ E., 33 lks. dist., marked $\frac{1}{4}$ S27 BT. CS

A fir, 15 ins. diam., bears S. 72° W., 41 lks. dist., marked $\frac{1}{4}$ S34 CS BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W

$\frac{1}{4}$ S 27
 $\frac{1}{4}$ S 34

1957

from which

A cedar, 19 ins. diam., bears N. 41° E., 47 lks. dist., marked $\frac{1}{4}$ S27 BT.

A fir, 18 ins. diam., bears S. $39\frac{1}{2}^{\circ}$ W., 48 lks. dist., marked