

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

1/4 S34 BT.

Deposit old corner material alongside iron post,

S. 87° 13' W., beginning new measurement.

Ascend 162 ft. over SE. slope, along N. edge of logged area.

1.77 Logging road, 15 lks. wide, bears N. 15° E. and S. 15° W.

6.12 Spur, slopes S.; descend 247 ft. over SW. slope.

9.36 Logging road, 15 lks. wide, bears N. and S.

13.93 Creek, 3 lks. wide, course S.; ascend 221 ft over broken SE. slope.

20.22 Point for the W 1/16 sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked

W 1/16 S 27 / S 34  
1957

*PER EDDIE JAMES SURVEY 4/18/19  
W 1/16 PORTION OUT OF  
POSITION - WILL BE  
CORRECTED - J.*

from which

A fir, 14 ins. diam., bears N. 20° W., 26 1/2 lks. dist., marked WL/16 S27 BT.

A white fir, 18 ins. diam., bears S. 1/2° E., 27 lks. dist., marked WL/16 S34 BT.

Ascend 341 ft. over broken SE. slope.

22.23 Logging road, 15 lks. wide, bears N. and S.

40.44 The cor. of secs. 27, 28, 33 and 34, determined at record distance from the remaining original bearing trees as follows:

A fir, 14 ins. diam., bears N. 42 1/4° E., 18 lks. dist., with an opened blaze, no scribe marks visible. (Record bearing N. 44° E.)

A sawed fir stump, 47 ins. diam., bears S. 35° E., 28 lks. dist.; no scribe marks visible, stump sawed low.

A sawed fir stump, 26 ins. diam., bears S. 67° W., 26 lks. dist., with an opened face, no scribe marks visible. (record bearing S. 65° W.)

At point for corner

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W  
S 28 | S 27  
S 33 | S 34  
1957

from which

A cedar, 15 ins. diam., bears N. 26 1/2° E., 31 lks. dist., marked T25S R4W S27 BT.

A cedar, 17 ins. diam., bears S. 74 1/2° E., 43 1/2 lks. dist., marked T25S R4W S34 BT.

A fir, 18 ins. diam., bears S. 54° W., 82 lks. dist., marked T25S R4W S33 BT.

A cedar, 12 ins. diam., bears N. 3 1/4° W., 100 lks. dist., marked T25S R4W S28 BT