

County Surveyor's Record, Douglas County, Oregon

33

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- 44.90 Creek, 3 lks. wide, course N. 20° W.; asc. 53 ft. over SW. slope.
- 48.20 Abandoned logging road, 15 lks. wide, bears N. 80° W. and SE.
- 53.04 Top of ascent, slopes W.; descend 39 ft. over NW. slope.
- 54.63 Logging road, 15 lks. wide, bears N. 15° E. and S. curving to SE.
- 56.50 Foot of descent, slopes W.; same logging road, 15 lks. wide, bears NW. and SE.; ascend 16 ft. over SW. slope.
- 58.39 Top of ascent, slopes W.; descend 36 ft. over NW. slope.
- 60.225 Point for the N 1/16 sec. cor. of secs. 27 and 28.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked
- | | | |
|------|--------|------|
| | N 1/16 | |
| | | |
| S 28 | | S 27 |
| | | |
| | 1957 | |
- from which
- A white fir, 10 ins. diam., bears S. 89° E., 24 lks. dist., marked N1/16 S27 BT.
- A white fir, 10 ins. diam., bears S. 68° W., 29 lks. dist., marked N1/16 S28 BT.
- Ascend 26 ft. over SW. slope.
- 62.70 Top of ascent, slopes W.; descend 223 ft. over NW. slope changing to N. slope.
- 75.96 Creek, 5 lks. wide, course W.; ascend 49 ft. over S. slope.
- 77.83 Logging road, 15 lks. wide, bears N. 85° W. and S. 80° E.
- 80.30 The cor. of secs. 21, 22, 27 and 28, determined from the original bearing trees, as follows:
- A sawed fir stump, 35 ins. diam., bears N. 55½° E., 34 lks. dist., with a healed blaze. (Record bearing N. 54° E.)
- A cedar, 21 ins. diam., bears S. 13° E., 39 lks. dist., marked with scribe marks 27 visible on opened blaze. (Record distance 36 lks.)
- A live cedar snag, 14 ins. diam., bears S. 31½° W., 20 lks. dist., with scribe marks S2 T2 R4 visible on opened blaze. (Record bearing S. 36° W.)
- A cedar, 25 ins. diam., bears N. 45° W., 15 lks. dist., with scribe marks S1 visible on opened blaze.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked
- | | | |
|------|----------|------|
| | T25S R4W | |
| | | |
| S 21 | | S 22 |
| | | |
| S 28 | | S 27 |
| | | |
| | 1957 | |
- from which
- A cedar, 5 ins. diam., bears N. 42° 45' E., 88½ lks. dist., marked T25S R4W S22 BT.