


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS
40.21

The point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, in field at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 60 ins. in the ground, with brass cap marked



Fd. M 93-17

from which


An apple, 6 ins. diam., located in fence row, bears N. 31° 40' E., $56\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S 15 BT.

A white oak, 11 ins. diam., bears N. 84° 25' W., $363\frac{1}{2}$ lks. dist., located in fence row, marked $\frac{1}{4}$ S16 BT.

Descend 9 ft. over valley bottom land through cultivated fields.

- 45.66 Woven and barbed wire fence, bears E. curving to S. and W.
- 45.96 Gravelled road, 25 lks. wide, bears N. 80° W. and S. 80° E. curving to S.
- 46.60 Woven and barbed wire fence, bears E. and W.
- 48.55 From this point, the NE. cor. of a wood frame machinery shed bears W. 325 lks. dist., dimensions 28x98 ft., long side bears S.
- 51.92 From this point the SE. corner of a wood frame barn bears W. 460 lks. dist., dimensions 58x60 ft., long side bears W.
- 55.37 From this point, the SE. cor. of a wood frame garage bears W. 521 lks. dist., dimensions 25x32 ft., long side bears N.
- 55.60 From this point, the SE. cor. of a wood frame house bears W. 654 lks. dist., dimensions 30x48 ft., long side bears N.; also from the same point, the NE. cor. of a wood frame shed bears W. 675 lks. dist., dimensions 18x40 ft., long side bears S.
- 58.69 Woven and barbed wire fence, bears E. and W.
- 67.25 Drainage ditch, 3 lks. wide, drains S. 70° W.; ascend 3 ft. over same cultivated field.
- 80.42 Point for the cor. of secs. 9, 10, 15 and 16, in field, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 48 ins. in the ground, with brass cap marked



from which

A cedar, 14 ins. diam., bears N. 43° 45' E., $322\frac{1}{2}$ lks. dist., marked T25S R4W S10 BT.

A pear, 6 ins. diam., bears S. 56° 45' E., 311 lks. dist., marked T25S R4W S15 BT., located in fence row.

A power and telephone pole, 12 ins. diam., bears S. $70\frac{1}{4}^\circ$ W., 702 lks. dist., with number 3H5w6 on metal tag.