

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A power and telephone pole, 12 ins. diam., bears N. 70 1/4° W., 897 lks. dist., with number 3H5-5 on metal tag.

A cedar post, cor. of fences extending N. and E., bears N. 22° 35' E., 27 lks. dist., marked X B0.

From this point, the cor. of secs. 3, 4, 9 and 10 bears North, 80.42 chs. dist., perpetuated by an iron pipe, 3 ft. long, 1 in. diam., firmly set 21 ins. in the ground, from which the remains of the original bearing tree:

A rotted and uprooted black oak, bears S. 4° W., 152 lks. dist., no marks remaining.

And trees marked by local surveyors

A rotted and burned fir snag, 10 ins. diam., bears N. 57 1/2° E., 13 1/2 lks. dist., with scribe marks S3 visible on burned blaze.

A burned fir snag, 24 ins. diam., bears S. 5 1/2° E., 27 lks. dist., with scribe marks T25S R4W S10 BT. visible on burned blaze.

A burned fir snag, 25 ins. diam., bears S. 76° 45' W., 24 lks. dist.; no marks remaining on burned blaze.

A rotted and burned fir stump, 18 ins. diam., bears N. 12 1/2° W., 17 lks. dist., no marks remaining on lower portion of burned blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

T25S R4W  
S 4 | S 3  
S 9 | S 10  
1957

from which

A fir, 9 ins. diam., bears N. 78 1/2° E., 60 1/2 lks. dist., marked T25S R4W S3 BT.

A cedar, 20 ins. diam., bears S. 31° E., 277 lks. dist., marked T25S R4W S10 BT.

A fir, 7 ins. diam., bears S. 57 1/2° W., 55 1/2 lks. dist., marked T25S R4W S9 BT.

A fir, 8 ins. diam., bears N. 12 1/2° W., 53 1/2 lks. dist., marked T25S R4W S4 BT.

Reset iron pipe alongside iron post.

From this same point the 1/4 sec. cor. of secs. 11 and 14, bears East, 119.47 chs. dist., perpetuated by the county surveyor in 1929 with a steel axle, 29 ins. long, 1 1/4 ins. diam., driven flush with surface of ground, from which the remaining original bearing tree:

A rotted ash stump, 14 ins. diam., bears N. 42° W., 14 lks. dist., with scribe marks BT visible on old rotted blaze.

and trees marked by the county surveyor in 1929

A white oak, 16 ins. diam., bears N. 42° W., 71 lks. dist., marked with a healed blaze.

A fir, 19 ins. diam., bears S. 29° E., 44 lks. dist., marked with a healed blaze.