

County Surveyor's Record, Douglas County, Oregon

38

Dependent Resurvey of Portion of Subdivisional Lines, T25 S., R. 4 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T25S R4W

 $\frac{1}{4}$ $\frac{S 11}{S 14}$

1957

from which

An ash, 10 ins. diam., bears N. 51° W., 14 lks. dist., marked $\frac{1}{4}$ S11 BT.A fir, 21 ins. diam., bears S. $29\frac{1}{2}^\circ$ W., 110 lks. dist., marked $\frac{1}{4}$ S14 BT.

Reset the axle alongside the iron post.

Corner falls alongside corner of fences extending N. and E.

Land, N. 40 chs. level; S. 20 chs., hilly. Soil, valley loam in N. portion; clay and loam in S. portion. Timber, scattering white and black oak; Undergrowth scrub oak and young fir.

From the cor. of secs. 28, 29, 32 and 33, determined at record distance from two remaining original bearing trees, as follows:

A burned and rotted fir snag, 31 ins. diam., bears N. $72\frac{1}{2}^\circ$ E., 30 lks. dist., with illegible scribe marks on 4 in. core in center of tree. (record bearing N. 60° E.)A sawed fir stump, 40 ins. diam., bears S. 17° W., 300 lks. dist., with scribe mark S visible on bruised and opened blaze. (Record bearing S. 10° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W

S 29 | S 28

S 32 | S 33

1957

from which

A fir, 24 ins. diam., bears N. $48^\circ 45'$ E., 195 lks. dist., marked T25S R4W S28 BT.A cedar, 25 ins. diam., bears S. $57\frac{1}{2}^\circ$ E., 164 lks. dist., marked T25S R4W S33 BT.A fir, 17 ins. diam., bears S. 37° W., 142 lks. dist., marked T25S R4W S32 BT.A fir, 7 ins. diam., bears N. $64\frac{1}{4}^\circ$ W., 214 lks. dist., marked T25S R4W S29 BT.N. $4^\circ 24'$ W., between secs. 28 and 29.

Ascend 99 ft. over S. slope, through scattering timber.

0.97 Woven-wire fence, bears E. and W.

5.58 Main divide between Calapooya Creek and North Umpqua River drainage, bears N. 50° E. and S. 50° W., also dirt road on top of ridge, 15 lks. wide, bears N. 50° E. and S. 50° W.; descend 267 ft. over NW. slope changing to N. slope.5.70 Woven-wire fence, bears N. 50° E. and S. 50° W.

13.10 Ravine, course W.; ascend 37 ft. over SW. slope.