

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

- Descend 30 ft. over NW. slope, through scattering timber.
- 1.17 Foot of descent, slopes W.; ascend 36 ft. over SW. slope.
- 5.45 Spur, slopes N. 70° W.; descend 223 ft. over N. slope.
- 13.45 Head of ravine, course NW.; descend 62 ft. over NW. slope.
- 18.28 Ravine, course W.; ascend 45 ft. over SW. slope.
- 21.08 Abandoned logging road, 10 lks. wide, bears NE. and SE.
- 22.19 Spur, slopes W.; descend 111 ft. over N. slope.
- 26.86 Ravine, course W.; ascend 122 ft. over SE. slope.
- 28.55 Abandoned logging road, 10 lks. wide, bears E. and W.
- 29.97 Abandoned logging road, 10 lks. wide, bears NE. and S. 60° W.
- 31.84 Abandoned logging road, 10 lks. wide, bears NE. and S. 70° W.
- 32.91 Spur ridge, bears N. 20° W. and SE.; descend 143 ft. over N. slope.
- 38.14 The cor. of secs. 29, 28, 20 and 21, determined at record bearing and distance from the only remaining original bearing tree as follows:

A fir, dead and down, 14 ins. diam., bears N. 60° W., 93 lks. dist., with scribe mark S visible in a burned and opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T25S R4W	
S 20	S 21
S 29	S 28
1957	

from which

A fir, 6 ins. diam., bears N. 85° E., 27 lks. dist., marked T25S R4W S21 BT.

A fir, 6 ins. diam., bears S. 74° E., 42 lks. dist., marked T25S R4W S28 BT.

A madrone, 8 ins. diam., bears S. 19½° W., 60 lks. dist., marked T25S R4W S29 BT.

A fir, 5 ins. diam., bears N. 60° W., 84½ lks. dist., marked T25S R4W S20 BT.

From this point, a locally established corner of secs. 20, 21, 28 and 29 bears S. 60° E., 23½ lks. dist., monumented with a ½ in. iron bar, 3 ins. above ground, firmly set, in a fence corner with fences extending N. and E.

from which

A fir, 4 ins. diam., bears N. 45° E., 19 lks. dist., marked S21 BT on a partially healed blaze.

A fir, 6 ins. diam., bears S. 57¼° E., 33 lks. dist., marked S28 BT on a partially healed blaze.

A fir, 6 ins. diam., bears S. 42° W., 29 lks. dist., marked S29 BT on a partially healed blaze.