

## County Surveyor's Record, Douglas County, Oregon

41

## Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A madrone, 9 ins. diam., bears N.  $5^{\circ} 45'$  W.,  $35\frac{1}{2}$  lks. dist., marked S20 BT.

Land, mountainous. Soil, loam and stony clay. Timber, fir, cedar, hemlock, yew, oak, maple and madrone; undergrowth, hazel, madrone, poison oak and fir reproduction.

From the cor. of secs. 15, 16, 21 and 22.

S.  $89^{\circ} 11'$  W., between secs. 16 and 21.

Descend 339 ft. over W. slope, through scattering timber.

14.93 Wire fence, bears S.  $25^{\circ}$  W. and N.  $25^{\circ}$  E.; enter cultivated field.

20.88 Wire fence at edge of field bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W. curving to S.

21.08 Dry bed of Banks Creek, 20 lks. wide; course N.  $35^{\circ}$  E.; ascend 113 ft. over SE. slope.

21.33 Enter cultivated field, bears N. and S.

23.07 Fence at edge of cultivated field, bears N.  $25^{\circ}$  E. and S.  $25^{\circ}$  W.

23.28 Dirt road, 20 lks. wide, bears N.  $20^{\circ}$  E. and S.  $20^{\circ}$  W.; enter open pasture land.

27.00 Spur, slopes SE.; descend 4 ft. along S. slope.

29.78 Wire fence, bears N.  $25^{\circ}$  E. and S.  $25^{\circ}$  W.

31.70 Ravine, course SE.; ascend 47 ft. over S. slope changing to SE. slope.

35.01 Power line; bears N.  $30^{\circ}$  W. and S.  $30^{\circ}$  E.

35.08 From this point the N. corner of a concrete water tank bears S.; 84 lks. dist., dimensions 8x8 ft., side bears SW.

35.96 Wet ravine, course SE.; ascend 72 ft. over E. slope.

40.245 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T25S R4W

$\frac{1}{4}$  S 16  
 $\frac{1}{4}$  S 21

1957

from which

A white oak, 13 ins. diam., bears N.  $30^{\circ} 45'$  E., 149 lks. dist., marked  $\frac{1}{4}$  S16 BT.

A fir, 12 ins. diam., bears S.  $46^{\circ}$  W.,  $92\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S21 BT.

Ascend 203 ft. over E. slope, through scattering timber and light undergrowth.

46.90 Ridge, bears NE. and SW.; descend 405 ft. over NW. slope changing to W. slope, through open pasture land.

60.55 Power line, bears N.  $20^{\circ}$  E. and S.  $20^{\circ}$  W.

62.51 From this point, the concrete smokestack of Bonanza Mine bears