

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS									
	bears Nort, 21.95 chs. dist.								
62.85	From this point the SE. corner of wood frame building of Bonanza Mine bears North, 19.24 chs. dist.								
63.33	From this point the SE. corner of a wood frame building of Bonanza Mine bears North, 17.23 chs. dist.								
63.65	From this point the center of mine shaft of Bonanza Mine bears North, 23.06 chs. dist.								
64.14	From this point the SE. corner of a wood frame building of Bonanza Mine bears North, 19.62 chs. dist.								
64.36	From this point the SE. corner of a wood frame building of Bonanza Mine bears North, 17.33 chs. dist.								
66.10	From this point the SE. corner of a wood frame building of Bonanza Mine bears North, 13.77 chs. dist.								
66.61	From this point the SE. corner of a wood frame house bears North, 8.06 chs. dist., dimensions 30x38 ft., long side bears N. 65° W.								
68.49	From this point the SE. corner of a wood frame house bears North, 4.60 chs. dist., dimensions 24x42 ft., long side bears N. 30° E.								
69.66	From this point the SE. corner of a wood frame house bears North, 4.07 chs. dist., dimensions 16x32 ft., long side bears N. 60° W.								
70.21	From this point the SE. corner of a wood frame house bears North, 3.18 chs. dist., dimensions 24x30 ft., long side bears N. 30° E.								
71.06	Wire fence bears N. 30° E. and S. 30° W.								
71.31	Dirt road, 25 lks. wide, bears N. 30° E. and S. 30° W.								
72.48	Foster Creek, 3 lks. wide, course N.; curving to NW.; ascend 163 ft. over NE. slope changing to E. slope.								
77.74	High voltage transmission line bears N. 17° E. and S. 17° W.								
80.49	<p>The corner of secs. 16, 17, 20 and 21, reestablished and recorded by the county surveyor by double proportionate measurement, in 1939, and locally accepted since that date; monumented with an iron pipe, 3/4 in. diam., firmly set, 12 ins. above ground, from which the county surveyor's bearing trees, as follows:</p> <p style="margin-left: 40px;">A cedar, 15 ins. diam., bears S. 36° W., 62 lks. dist., with scribe marks S20 T25S R4 CS BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir snag, 40 ins. diam., bears N. 55° W., 107 lks. dist., with scribe marks S17 T25S R4W CS visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T25S R4W</td></tr> <tr><td>S 17</td><td>S 16</td></tr> <tr><td>S 20</td><td>S 21</td></tr> <tr><td colspan="2">1957</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 62° E., 41½ lks. dist., marked T25S R4W S16 BT.</p>	T25S R4W		S 17	S 16	S 20	S 21	1957	
T25S R4W									
S 17	S 16								
S 20	S 21								
1957									

Fd by
 Rbt. Dolan
 Oct 1982
 M 93-19