

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A fir, 10 ins. diam., bears N. 33° E., 118½ lks. dist., marked
¼ S16 BT.

A fir, 6 ins. diam., bears S. 30¼° W., 62 lks. dist., marked
¼ S17 BT.

Descend 53 ft. over NW. slope.

43.67 Head of ravine, course W.; ascend 57 ft. over SW. slope.

48.48 Spur slopes NW.; descend 196 ft. over N. slope.

53.46 Ravine, course NW.; ascend 120 ft. along W. slope, changing to SW. slope.

58.13 Spur, slopes NW.; descend 79 ft. over N. slope.

60.63 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

N 1/16	
S 17	S 16
1957	

from which

A fir, 15 ins. diam., bears S. 85¼° E., 113 lks. dist., marked
N 1/16 S16 BT.

A fir, 20 ins. diam., bears N. 44¼° W., 123 lks. dist., marked
N 1/16 S17 BT.

Descend 36 ft. over N. slope.

61.65 Ravine, course W.; ascend 157 ft. over SW. slope.

68.44 Skid road, on spur ridge, bears NW. and SE.; descend 367 ft. over N. slope, through partly logged area.

71.32 Skid road, bears E. and W.

75.83 Trail, bears N. 80° W. and S. 80° E.

80.84 The cor. of secs. 8, 9, 16 and 17, determined at record bearing and distance from the remaining original bearing trees:

A sawed and rotted fir stump, 70 ins. diam., bears S. 60° E.,
57 lks. dist., with no marks remaining on a chopped-out blaze.

At the corner point

Set an iron post., 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T25S R4W	
S 8	S 9
S 17	S 16
1957	

from which

A fir, 7 ins. diam., bears N. 55¼° E., 50 lks. dist., marked
T25S R4W S9 BT.

A madrone, 6 ins. diam., bears S. 16° 45' E., 63 lks. dist.,
marked T25S R4W S16 BT.

A fir, 6 ins. diam., bears S. 67° 45' W., 38½ lks. dist., marked
T25S R4W S17 BT.

A fir, 12 ins. diam., bears N. 59° 45' W., 75½ lks. dist.,
marked T25S R4W S8 BT.

Fd. by:
 Rbt. DOLAN
 Oct. 1982
 M 93-19