

County Surveyor's Record, Douglas County, Oregon

45

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

From this point, an iron pipe, 1 in. diam., 14 ins. above the ground, set by county surveyor in 1939, bears N. 58° W., 4 lks. dist. from which local bearing trees:

A fir, 24 ins. diam., bears S. 21 $\frac{1}{2}$ ° W., 162 lks. dist., with bark scribed S17 CS BT.

An oak, 22 ins. diam., bears N. 43 $\frac{1}{2}$ ° W., 183 lks. dist., with a healed blaze.

From this same point, United States Coast & Geodetic Survey triangulation station BANKS 1953, bears N. 65° 58' E., 36.29 chs. dist.

Land, mountainous. Soil, rocky clay and loam. Timber, scattered fir, madrone and oak. Undergrowth, hazel, manzanita, vinemaple, scrub oak and reproduction.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 49' W., between secs. 9 and 16.

Descend 21 ft. over gradual W. slope, through cultivated field.

7.39 Power and telephone line, bears N. 15° W. and S. 15° E.

12.87 Fence, bears N. and S.; leave field and enter creek bottom, through timber.

13.72 Banks Creek, 10 lks. wide, course N.; ascend 22 ft. over E. slope changing to NE. slope.

14.92 Leave timber, edge bears N. and S.; enter open field.

23.59 Dry branch, 3 lks. wide, course N.; ascend 93 ft. over NE. slope changing to E. slope.

24.73 Fence at edge of field bears N. 10° W. and S. 10° E.

24.93 Gravelled road, 25 lks. wide, bears N. 10° W. and S. 10° E. curving to SE.

25.12 Fence, bears N. 10° W. and S. 10° E.

25.52 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

29.21 Fence, bears N. 30° E. and S. 30° W. Enter open pasture.

32.34 Ditch, drains SE.; enter timber and undergrowth.

39.86 The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, perpetuated with a broken drill bit 2 ft. long, 1 in. diam., firmly set, 22 ins. in the ground, and a fir post, 5 ins. cross section, firmly set, 4 ft. above ground. In the county records, dated June 1939, reference is made that this corner has been recently renewed by Deputy Surveyor Boyer, but no additional information has been recorded. This corner has been locally accepted and I accept it as the best available evidence. The following bearing trees have been locally established but are not recorded:

A fir snag, 24 ins. diam., bears S. 0° 30' W., 50 $\frac{1}{2}$ lks. dist., bark scribed X BT.

A fir snag, 23 ins. diam., bears S. 32 $\frac{1}{2}$ ° W., 54 lks. dist., marked CS BT on partly opened blaze, also bark scribed $\frac{1}{4}$ S16 T25S R4.

A sawed fir stump, 30 ins. diam., bears N. 26° W., 42 lks. dist., marked CS BT on opened blaze.

Fd. M 93-17