

## County Surveyor's Record, Douglas County, Oregon

48

Dependent Resurvey of Portion of Subdivision, T. 25 S., R. 4 W.

CHAINS	
4.85	Ravine, course SW.; curving to W.; descend 143 ft. along general N. slope on S. side of ravine.
16.54	Spur, slopes NW.; descend 26 ft. over W. slope.
20.70	Point for the W 1/16 sec. cor. of secs. 29 and 32. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked $\begin{array}{r} \text{W } 1/16 \text{ } \frac{\text{S } 29}{\text{S } 32} \\ 1957 \end{array}$ from which A fir, 5 ins. diam., bears N. 16½° W., 158 lks. dist., marked W 1/16 S29 BT. A yew, 7 ins. diam., bears S. 51° 45' E., 64 lks. dist., marked W 1/16 S32 BT. Descend 7 ft. over W. slope.
21.00	Dry creek bed, course N.; ascend 127 ft. over E. slope.
24.42	Spur, slopes N. 10° E.; ascend 61 ft. over NE. slope.
29.54	Abandoned logging road, 10 lks. wide, bears NE. and SW. on spur, slopes NE.; ascend 159 ft. over NE. slope.
33.95	Abandoned logging road, 10 lks. wide, on spur ridge, nears N. and S.; descend 250 ft. over W. slope.
38.50	Spring branch, 1 lk. wide, course NW.; ascend 71 ft. over NE. slope.
41.40	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked $\begin{array}{r} \text{T25S R4W} \\ \text{S } 30 \text{   } \text{S } 29 \\ \text{S } 31 \text{   } \text{S } 32 \\ 1957 \end{array}$ from which A hemlock, 6 ins. diam., bears N. 46° E., 33 lks. dist., marked T25S R4W S29 BT. A fir, 23 ins. diam., bears S. 50° E., 62 lks. dist., marked T25S R4W S32 BT. A fir, 12 ins. diam., bears S. 4° 45' W., 192 lks. dist., marked T25S R4W S31 BT. A hemlock, 50 ins. diam., bears N. 36° W., 368 lks. dist., marked T25S R4W S30 BT. From this point the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp. bears S. 1° 38' W., 80.48 chs. dist., determined at record bearing and distance from the original bearing trees as follows: A black oak, 35 ins. diam., bears N. 35° E., 75 lks. dist., marked with a healed blaze. A down and rotted black oak, 14 ins. diam., bears S. 69° E., 58 lks. dist., no scribe marks visible.