

## County Surveyor's Record, Douglas County, Oregon

49

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

A down and rotted black oak, 30 ins. diam., bears S. 34° W., 150 lks. dist., with scribe marks S6 BT visible on opened blaze.

A down and rotted black oak, 30 ins. diam., bears N. 31° W., 71 lks. dist., no scribe marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T25S R4W	
S 31	S 32
S 6	S 5
T26S	
1957	

from which

A white oak, 10 ins. diam., bears N. 66° E., 20 lks. dist., marked T25S R4W S32 BT.

A white oak, 10 ins. diam., bears S. 27½° E., 44 lks. dist., marked T26S R4W S5 BT.

A white oak, 10 ins. diam., bears S. 32° W., 44 lks. dist., marked T26S R4W S6 BT.

A white oak, 11 ins. diam., bears N. 63½° W., 23 lks. dist., marked T25S R4W S31 BT.

From this same point the cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp. bears S. 89° 47' W., 82.64 chs. dist., perpetuated with a fir stake, 3 ins. in cross section, 4 ft. above ground, from which the original bearing trees, as follows:

A fir, 35 ins. diam., bears N. 63° E., 32 lks. dist., with a healed blaze.

A fir stump, 35 ins. diam., bears S. 40° E., 34 lks. dist., with no scribe marks visible on opened blaze.

A fir, 22 ins diam., bears S. 7° W., 43 lks. dist., with a healed blaze.

A fir, 47 ins. diam., bears N. 75° W., 60 lks. dist., with scribe marks S25 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T25S	
R5W	R4W
S 25	S 30
S 36	S 31
1957	

from which

A fir, 20 ins. diam., bears N. 36½° E., 132 lks. dist., marked T25S R4W S30 BT.

A fir, 23 ins. diam., bears S. 25½° E., 218 lks. dist., marked T25S R4W S31 BT.

A cedar, 6 ins. diam., bears S. 65½° W., 65 lks. dist., marked T25S R5W S36 BT.

A cedar, 10 ins. diam., bears N. 42½° W., 71 lks. dist., marked T25S R5W S25 BT.