

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines, T25 S., R. 4 W.

CHAINS	<p>Deposit old corner material alongside iron post.</p> <p>Land, mountainous. Soil, loam and stony clay. Timber, fir, cedar, yew, oak, maple and madrone. Undergrowth, hazel, vinemaple, salal, and fir reproduction.</p> <hr/> <p>N. 4° 37' W., between secs. 29 and 30.</p> <p>Descend 230 ft. over N. slope changing to NE. slope, through scattering timber of logged area.</p> <p>20.027 Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <p>S 1/16</p> <p>S30 S 29</p> <p>1957</p> </div> <p>from which</p> <p>A maple, 17 ins. diam., bears S. 88½° E., 48 lks. dist., marked S1/16 S29 BT.</p> <p>A fir, 8 ins. diam., bears S. 37° 45' W., 108 lks. dist., marked S1/16 S30 BT.</p> <p>Descend 99 ft. over NE. slope.</p> <p>30.48 Skid road, 20 lks. wide, bears S. 10° W. and N. 10° E. curving to NW.</p> <p>33.38 Creek, 5 lks. wide, course N. 30° W.; ascend 19 ft. over SW. slope.</p> <p>40.055 Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <p>T25S R4W</p> <p>¼</p> <p>S 30 S 29</p> <p>1957</p> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears S. 27½° E., 35 lks. dist., marked ¼ S29 BT.</p> <p>A fir, 8 ins. diam., bears N. 27¼° W., 7 lks. dist., marked ¼ S30 BT.</p> <p>Descend 69 ft. over NW. slope.</p> <p>42.87 From this point the SE. cor. of a wood frame barn bears W., 257 lks. dist., dimensions 22x24 ft., long side bears W.</p> <p>44.53 Dirt logging road, 30 lks. wide, bears NE. and SW.</p> <p>46.94 Sutherlin Creek, 5 lks. wide, course S. 70° W.; ascend 379 ft. over SE. slope.</p> <p>53.19 Skid road, 20 lks. wide, bears NE. and SW.</p> <p>58.21 Skid road, 20 lks. wide, bears NW. and SE.</p> <p>60.082 Point for the N 1/16 sec. cor. of secs. 29 and 30.</p>
--------	--