

County Surveyor's Record, Douglas County, Oregon

51

Dependent Resurvey of Portion of Subdivisional Lines, T. 25 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} N\ 1/16 \\ | \\ S\ 30\ | \ S\ 29 \\ | \\ 1957 \end{array}$$

from which

A madrone, 17 ins. diam., bears N. 21° E., 171 lks. dist., marked N1/16 S29 BT.

A fir, 15 ins. diam., bears S. $6\frac{1}{2}^\circ$ W., 140 lks. dist., marked N1/16 S30 BT.

Ascend 467 ft. over SE. slope.

67.47 Skid road, 20 lks. wide, bears NW. and SE.

80.11 The cor. of secs. 19, 20, 29 and 30, determined by the original cor. tree, a fir, 45 ins. diam., with healed blazes in each of the four quadrants; from which the original bearing trees, as follows:

A down madrone, 31 ins. diam., bears N. 48° W., 65 lks. dist., no scribe marks visible.

A down madrone, 16 ins. diam., bears S. 45° E., 21 lks. dist., with a rotted blaze; no scribe marks visible. (Record calls for a laurel.)

A madrone stump hole, bears S. 48° W., 30 lks. dist.

A fir, 20 ins. diam., bears N. 50° W., 31 lks. dist., with T2 RW S19 visible on opened blaze. (The record calls for a laurel.)

establish new bearing trees

A fir, 32 ins. diam., bears N. 51° E., 130 lks. dist., marked T25S R4W S20 BT.

A fir, 18 ins. diam., bears S. $49\frac{1}{2}^\circ$ E., 104 lks. dist., marked T25S R4W S29 BT.

A fir, 10 ins. diam., bears S. $19^\circ 45'$ W., 158 lks. dist., marked T25S R4W S30 BT.

Land, mountainous. Soil, clay and stony clay. Timber, fir, cedar, hemlock, madrone, maple and dogwood; undergrowth, hazel, salal, fir reproduction, madrone and dogwood.

From the cor. of secs. 20, 21, 28 and 29.

N. $88^\circ 22'$ W., between secs. 20 and 29.

Ascend 44 ft. over E. slope, through heavy timber and dense reproduction.

2.66 Spur ridge, bears N. and S.; descend 326 ft. over W. slope.

13.13 Abandoned logging road, 10 lks. wide, bears N. and S.

14.10 Foster Creek, 3 lks. wide, course N. 20° E.; ascend 253 ft. over E. slope.

14.44 Graded access road, bears N. 20° E. and S. 20° W., 15 lks. wide.

21.34 Dirt road, 10 lks. wide, on main ridge between Foster Creek and Sutherlin Creek, bears N. and S.; desc.; 369 ft. over NW. slope.